

LTH12-100

Lithium iron phosphate battery



Characteristics

Characteristics		
Electrical		
Nominal voltage		12.8V
Nominal capacity at 5 hours rate (25°C)		100Ah
Energy		1280Wh
Charge Efficiency at 0.2C (25°C)		99.5%
Discharge Efficiency at 1C (25°C)		96-99%
Approx. internal resistance (25°C)		≤14.0 mΩ
Cycle life / 0.2C 100% D.O.D		>2000 cycles
Capacity affected by temperature	40°C	101%
	25°C	100%
	0°C	90%
	-10°C	75%
Mechanical		
Dimensions	Length	330±2mm (12.99inch)
	Width	172±2mm (6.73inch)
	Height	215±2mm (8.43inch)
	Total height	220±2mm (8.66inch)
Terminal type		T16 (M8)
Torque		2.3±2.5N.m
Weight		12.5kg (39.24lbs)±4%
Water & Dust resistance		IP65
Battery container ABS UL94-HB		V-0 optional
Cell strings		4 strings
Temperature		
Nominal operating	temperature	25°C±3 (77±5°F)
Operating temperature range	Discharge	-20°C~60°C (-4°F~140°F)
	Charge	0°C~45°C (32°F~113°F)
	Storage	0°C~40°C (32°F~104°F)
Charging		
Charging voltage at 25°C		14.6V
Standard charge mode (25°C±2°C, <75%RH)		0.2CA Constant Current to 14.6V, then Constant Volt- age 14.6V until the current drops to 0.02CA. Rest 30 minutes, before use.
Nominal charging current		20A
Maximum charging current		50A
Charging cut-off voltage		14.6V
Discharging		
Continuous discharge current		100A
Maximum pulse discharge current (<100ms)		300A
Discharge cut-off voltage		11.2V
Self discharge rate (25°C)		≤3%/month
Comunication &		
Communication protocol (optional)		RS485 (standard none)
SOC (optional)		LED/Bluetooth
Maximum modules in paralel or series		4 string 6 parallel

Overview

Lithium-Iron Phosphate batteries offer superb improvement in characteristics compared to lead-acid technology. Due to the extreme cycle and calendar life, LiFePO4 batteries are an excellent long-term investment for your applications. Powerful, lightweight, safe, and smart, the Lithium-Iron Phosphate batteries are the future of the energy storage you can have right now.

Features

Longer cycle life - Up to 15 times longer cycle life and 5 times longer float/calendar life than lead-acid batteries.

More capacity - Provides up to 100% of usable energy.

Lightweight - 60% lighter than lead-acid batteries.


High discharge rate - Ability to fully discharge the battery at a high rate of discharge.

Fast charging - Charges much faster than conventional sealed lead-acid batteries.

Long cycle life - More than 2000 cycles at 100% depth of discharge.


Intelligent BMS - The battery management system monitors and adapts to battery conditions to maximize performance and safety.

Dimensions & Terminal Type (mm)







Discharge characteristics (25°C)




Temperature effects on discharge (0.5C)




Charging Time on S.O.C. (25°C)



Charge characteristics (25°C)



Cycle life on D.O.D. (25°C)



D.O.D. - depth of discharge S.O.C. - state of charge

Self discharge characteristics

