

Eaton 248397

Catalog Number: 248397

Z-MS-6,3/2. Motor-Protective Circuit-Breakers, 4-6, 3A, 2 p



General specifications

Product Name	Catalog Number
Eaton Distribution parts	248397
EAN	Product Length/Depth
4015082483975	80 mm
Product Height	Product Width
75 mm	36 mm
Product Weight	Compliances
0.244 kg	RoHS conform
Model Code	
Z-MS-6,3/2	

Specyfikacje produktu

Actuator type

Rocker lever

Switch off technique

Magnetic

Adjustment range short-term delayed short-circuit release - min

63 A

Adjustment range undelayed short-circuit release - max

82 A

Adjustment range undelayed short-circuit release - min

63 A

Heat dissipation per pole, current-dependent

2.55 W

Overload release current setting - max

6.3 A

Overload release current setting - min

4 A

Rated operating power at AC-3, 230 V

0 kW

Rated operating power at AC-3, 400 V

2.2 kW

Rated operating voltage (Ue) - max

400 V

Rated operating voltage (Ue) - min

400 V

Rated operational current for specified heat dissipation (In)

6.3 A

Rated short-circuit breaking capacity at 400 V AC

10 kA

Rated uninterrupted current (Iu)

6.3 A

Fitted with:

Thermal protection

Degree of protection

IP20

Equipment heat dissipation, current-dependent

Do pobrania

Deklaracje zgodności

DA-DC-03_Z-MS

DWG

[eaton-dimensions-mas-ms7.jpg](#)

[eaton-wiring-diagram-ms7-2p.jpg](#)

[MAS_MS7](#)

DWG

[eaton-3d-drawing-diagr-ms-40a.jpg](#)

[Diagr_MS_40A](#)

mCAD model

[eaton-cadenas-side_view-z_ms_2p_side.pra](#)

[eaton-cadenas-path-z_ms_motorschutzscharter-z_ms_2p.3db](#)

[eaton-cadenas-front_view-z_ms_2p_front.pra](#)

Schematy połączeń

[MS7_2p](#)

5.1 W

Device construction

Complete device in housing

Electrical connection type of main circuit

Screw connection

Number of poles

Two-pole



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia