







UV FILTER

© ARDON SAFETY s.r.o. / ALL RIGHTS RESERVED





SAFETY SPECTACLES

ARTIKLE NO.

E4289 (Smoke)

MATERIAL lens MATERIAL temples LENS polycarbonate polycarbonate Smoke



DESCRIPTION

Offers optimum eye protection in all situations. The soft component connected directly with the top of the lens offers higher protection against dust and water. Thanks to the modern and innovative shape spectacles adapt perfectly to the wearer's face and provide excellent wearer comfort and 100 % protection.

Suitable for wearing with Earmuffs nad helmets. Wraparound style lens offer excellent views. Clear polycarbonate lens offers UV 400 protection. Protection against high-speed particles - low energy (F), Protection against high-speed particles at extreme temperatures (T). Conforms to K&N due to the lens been coated with anti-scratch and anti-fog treatment. Provides excellent colour recognition, protects against reflection and glare. Suitable for outdoor work, construction sites, road works, driving vehicles, sports activities.

© ARDON SAFETY s.r.o. / ALL RIGHTS RESERVED



STANDARDS

This personal protective equipement is in conformity with these harmonized European Standards.

EN 166:2001:	Personal eye protection – General requirements.
EN 170:2002:	Personal eye protection – Ultraviolet filters – Transmittance
	requirements and recommended use.
EN 172:1994+A1+A2	Personal eye protection – Sunlight filters for industrial use.

Certified by Notified body No. 0598 (SGS FIMKO, Takomotie 8, FI-00380, Helsinki, Finland), certificate No. 0598/PPE/23/2893, dated 16th of May 2023.

Lens Smoke, UV 400, 5-3.1 1 AR 1 FT KN

Type of filter	5	UV filter
Shade number	3.1	Smoke
Optical class	1	pernament use
Mechanical resistance	FT	Resistance to surface damage by fine particles (F) and protection against high speed particles at

Adjustment of temples in lenght	x	
Adjustment of temples in inclination	x	
Anti-fog lens	\checkmark	
Anti-scratch lens	\checkmark	FA
UV	√	UV400



extreme temperatures -

5°/+55° C (T).



PIECES IN CARTON300 pcsPIECES IN A BOX10 pcsWEIGHT OF A CARTON17kgSIZE OF A CARTON0,103 m³UNIT PACKING (POLYBAG)1 pc

Store in dry and dark enviroment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents. It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.

