

64623 HLX

Halogen (< 75 V) Single End



Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- HLX lamps provide 10% higher luminous flux with same power consumption over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable



Product datasheet

Technical data

General Product Information

Product number (Americas)	54251
Product name (Americas)	EVA 64623 HLX 100W 12V 40/CS 1/SKU
Family brand	XENOPHOT (HLX)
ANSI code	EVA
LIF code	M/28
Global order reference	64623 HLX


Electrical Data

Nominal wattage	100 W
Nominal voltage	12 V
Type of current	AC

Photometric Data

Nominal luminous flux	2800 lm
Illuminated field	4.7*2.7 mm ²
Color temperature	3300 K
Color rendering index Ra	100
Light center length (LCL)	30.0 mm
Light center length (LCL) - (in)	1.17 in

Physical Attributes & Dimensions



Lamp base	GY6.35
Diameter (in)	0.472 in
Diameter	11.5 mm
Length	44.0 mm
Product weight	2.50 g

Product datasheet

Operating Conditions

Burning position	s90
------------------	-----

Lifetime Data

Nominal lifetime	1500 hr
------------------	---------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300012018 4008321037213
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300012018	OSRH64623HLX40	-	-	-
4050300012018	OSRH64623HLX40	-	-	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321037213	64623 HLX	Folding carton box 100	178 mm x 178 mm x 54 mm	1.71 dm ³	324.00 g
4008321037220	64623 HLX	Shipping carton box 1000	365 mm x 190 mm x 295 mm	20.46 dm ³	4991.00 g
4050300012018	64623 HLX	Folding carton box 1	- x - x -		
4050300890630	64623 HLX	Shipping carton box 40	150 mm x 113 mm x 118 mm	2.00 dm ³	290.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
