

KARTA TECHNICZNA



ŁADOWALNA CZOŁÓWKA LED

VIDEX®



IP65



Not Dimmable



Free

GWARANCJA 2 LATA

NEUTRAL WHITE



5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Neutrálno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Wymienne źródło światła nie

Rodzaj źródła światła

Możliwość przyciemniania nie

Technologia LED

Parametry elektryczne

Moc w trybie włączenia (Pon) 5 W + COB

Interfejs wejściowy Micro USB

Parametry fotometryczne

Użyteczny strumień świetlny źródła światła (Φuse) 310 Lm

Temperatura barwowa światła 5000K (neutralny biały)

Szczytowa intensywność światła 1380 cd

VIDEX VLF-H025C 330Lm 5000K

INDEKS: VLF-H025C

Dodatkowe informacje

Kolor obudowy	Czarny
Klasa ochrony IP	IP65
Zakres temperatur pracy	-20° +40°C
Materiał obudowy	PC
Zawartość rtęci	nie

Wymiary

Kod EAN	4820246481076
Wysokość	46 mm
Opakowanie zbiorcze	20 szt.
Szerokość	70 mm
Masa netto jednostki	99g
Głębokość	38 mm
W paczce	1 szt.

Znaki oznaczające towary

Oznakowanie opakowań CE, Utylizacja

VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEKS: VLF-H025C



VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEKS: VLF-H025C

VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEKS: VLF-H025C



VIDEX®
MODEL | H025C

RECHARGEABLE LED HEADLAMP
WITH SENSOR



310
MAX LUMENS

1800mAh
RECHARGEABLE

DUAL
LIGHT

IP65
SHOCKPROOF

1m
RED LIGHT

RED LIGHT

VIDEX®
MODEL | H025C



MAIN LED CREE
XTE 5W 5000K
(Neutral white)

LOW BEAM LED
COB 5W 5000K
(Neutral white)

85° Beam angle and 74m max illumination distance.
120° Beam angle and 7m max illumination distance.
Both light sources can work together reaching max brightness
310 lumens.

VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEKS: VLF-H025C

VIDEX®

MODEL | H025C

TEXTURED REFLECTOR



Textured reflector provides even yet long lighting beam.

VIDEX®

MODEL | H025C

LOW BEAM LED



A wide-angle LED perfectly copes with the task of lighting the near space.

VIDEX®

MODEL | H025C

SWIFT TOUCHLESS CONTROL



With built-in motion sensor you can turn on/off the light by a hand wave.

VIDEX®

MODEL | H025C

POWER BUTTON

SENSOR BUTTON



POWER BUTTON. Turns on/off the light and changes the modes. Press and hold for COB light.

SENSOR BUTTON. Press to activate the sensor for further control by a hand wave.

VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEKS: VLF-H025C



VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEKS: VLF-H025C

VIDEX®

MODEL | H025C

MICRO-USB PORT



Full charge for around 3 hours.
The charging port covered by thick silicone, which prevents dust and water penetrate inside the device.

VIDEX®

MODEL | H025C

1800mAh. 600 CYCLES



Built-in Li-polymer rechargeable can run for around 10 hours at one cycle and can replace thousands of primary batteries during its service life. An intelligent charge control circuit protects the battery from overdischarge and overcharge.

VIDEX®

MODEL | H025C

NYLON HEADBAND



The headband is made of nylon, which is an elastic and wear-resistant material.

VIDEX®

MODEL | H025C

TILT MECHANISM



Adjust the headlamp tilt angle within 45 degrees.

VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEKS: VLF-H025C



Zastrzegamy sobie prawo do zmian technicznych. Dane zawarte w tym materiał nie jest prawnie wiążący.

Allegro Opt Sp. z oo, Handlowa 23, 05-120 Legionowo, Polska.

Data: 19.10.2023