

Mini Pipe Plugs



Web Page



WhatsApp



E-mail

TAPASAN Mini Pipe Plugs are used to temporarily blocking pipelines with short pipe lengths. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C. It is ideal for blocking lines where standard pipe plugs are long. The most important advantage is that it has a wide diameter range.

*It can be produced with NBR rubber resistant to gas, petroleum and derivatives.

Product Code : KBM



Connection Type
(R 1/4")



Technical Details
Label



Friction Increasing
Design

Product Code	Size Usage Range		Max. Working Pressure (bar) / (psi)	Deflated Plug Dimensions		Back Pressure (bar) / (psi)	Approx. Weight (kg) / (lbs)
	Min. Diameter	Max. Diameter		Diameter	Total Length		
	(mm) / (inch)	(mm) / (inch)		(mm) / (inch)	(mm) / (inch)		
KBM50100	50 / 2"	100 / 4"	2.5 / 36	45 / 1.8"	195 / 7.6"	0.3 / 4.4	0.3 / 0.66
KBM70150	70 / 2.8"	150 / 6"	2.5 / 36	65 / 2.6"	250 / 9.8"	0.3 / 4.4	0.4 / 0.88
KBM100200	100 / 4"	200 / 8"	3.0 / 44	88 / 3.5"	250 / 9.8"	0.3 / 4.4	0.7 / 1.5
KBM150300	150 / 6"	300 / 12"	2.5 / 36	140 / 5.5"	350 / 13.7"	0.3 / 4.4	1.2 / 2.6
KBM200400	200 / 8"	400 / 16"	2.5 / 36	187 / 7.4"	450 / 17.7"	0.3 / 4.4	1.8 / 3.9