

4 Channel Constant Voltage DALI LED Dimmer

Model No.: DA4

4 Address/4 Channel/Constant voltage/PWM dimming



C€ RoHS

Features

- 4 channel constant voltage DALI LED Dimmer, 5A per channel.
- 4 DALI address, 4 channel work separately.
- In accordance with DAU standard protocol IEC 62386-102, IEC 62386-207 and in compliance with DAU products from other international incorporation.
- DALI address will be automatically assigned by DALI master.
- PWVM digital dimming, standard DALI logarithmic dimming curve.
- Over-load / Short circuit protection, recover automatically.

Technical Parameters

Input and Output	
Input voltage	12-24VDC
Input current	20.5A
Output voltage	12-24VDC
Output current	4CH,5A/CH
Output power	4 × (60-120)W
Output type	Constant voltage

Dimming data	
nput signal	DAU
Dimming range	0-100%
Dimming curve	Logarithmic
WM Frequency	2000Hz (default)

Warranty and Protection	n
Warranty	5 years
Protection	Reverse polarity Over-load Short circuit

Environment	
Operation temperature	Ta: -30°C ~ +55°C
Case temperature (Max.)	Tc:+85°C
IP rating	IP20

Mechanical Structures and Installations





Wiring Diagram



DALI control

This product is designed with 4 DAU address input and 4 channel output, DAU address is assigned by DAU Master controller automatically, please refer to user manuals of compatible DAU Masters for specific operations.

Safety & Warnings

• DO NOT install with power applied to device.

• DO NOT expose the device to moisture.