

# LogiLink®



## 4K HDMI Splitter, 1x2 Ports 4K/60 Hz, Downscaler

Art. No.: HD0059


This 4K HDMI Splitter with HDCP 2.2 is an advanced solution for splitting a single HDMI input to two HDMI outputs. It provides high performance audio and video output up to UHD 4K@60 Hz resolution and delivers up to 18 Gbps of bandwidth, ensuring the best 4K picture quality.

### Features:

- » Connects one HDMI source to two HDMI displays at the same time
- » Video resolution up to UHD 4K@60 Hz (YUV 4:4:4) and Full 3D
- » Bandwidth up to 18 Gbps (6 Gbps at 600 MHz per channel)
- » Compliant with HDCP 2.2
- » Supports 36 bit Deep Color (12 bit per channel)
- » Supports DDC, HDR, CEC, EDID and downscaler function
- » Supports LPCM 7.1, Dolby TrueHD and DTS-HD Master Audio
- » Perfect solution for home, bars and restaurants



- (a) HDMI output 1 & 2 port
- (b) HDMI input port
- (c) USB-C DC 5 V input
- (d) HDMI output 1 & 2 LED indicator
- (e) Downscaler LED indicator
- (f) Power switch



The „Downscaler“ function allows the product to display the 4K input resolution on two screens/monitors with different maximum resolutions (e.g. 1080p and 4K) simultaneously. This is useful, for example, when using an older Full HD (1080p) monitor and a newer Ultra HD (4K) monitor at the same time.



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.

## Specifications:

Input Port	1x HDMI-A female, 1x USB-C female
Output Ports	2x HDMI-A female
HDMI Standard	2.0
HDCP Version	2.2
Output Resolution	480i/60 Hz, 576i/50 Hz, 1080i/50/60 Hz, 480p/60 Hz, 576p/50 Hz, 720p/50/60 Hz, 1080p/24/25/30/50/60 Hz, 4K@24/25/30 Hz, 4K@50/60 Hz 4:4:4
Video Bandwidth	Up to 18 Gbps
EDID Management	Yes (copy and downscaler)
CEC (Consumer Electronics Control)	Yes
HDR (High-Dynamic Range)	Yes
DDC (Display Data Channel)	Yes
TMDS (Transition Minimized Differential Signaling)	Yes
LED Indicator	Yes
3D Supporting	Yes
Chassis Material	ABS
Power By	Charge thru USB-C port (DC 5 V/1 A, 5 W)
Uncompressed Audio	LPCM 7.1
Compressed Audio	DTS, Dolby Digital, DTS-HD Master Audio, Dolby TrueHD
Operating Temperature	0–70°C
Operating Humidity	10–85% RH (no condensation)
Dimensions	10.2 x 4.48 x 1.45 cm
Weight	47 g
Cable Length	1 m
Color	Black

## Package Contents:

- » 1x HDMI Splitter
- » 1x USB Charging Cable
- » 1x User Manual

## Package Information:

- » Packing Dimension: 167 x 110 x 52 mm
- » Packing Weight: 0.145 kg
- » Carton Dimension: 575 x 255 x 360 mm
- » Carton Q'ty: 40 pcs
- » Carton Weight: 6.5 kg



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.

