



Rally Special 10W-60

SPECIFICATIONS

SAE: 10W-60

API: SM

ACEA: A3/B3

APPROVALS AND CONFORMITY

MB 229.5 VW 501.01/505.00 Porsche A40

CHARACTERISTICS

- High wear protection;
- Excellent viscosity-temperature behaviour;
- Minimal frictional loss;
- High cleaning capability;
- High oxidation and temperature stability;
- Prevents black sludge formation.

EFFECTS

- Excellent cold starting behaviour;
- Very good operating reliability;
- Optimises motor performance;
- Optimal engine cleanliness;
- Low oil consumption;
- High margin of performance and high product stability;
- All-year operation.

TYPICALS

Specific weight at 15 °C, kg/m³	865
Viscosity at -30 °C, cP	6910
Viscosity at 40 °C, cSt	184
Viscosity at 100 °C, cSt	26.0
Viscosity index, -	177
Flash point COC, °C	222
Pour point, °C	-36
TBN, mgKOH/g	13

DESCRIPTION

Wolver Rally Special SAE 10W-60 is a HC-Synthetic engine oil for highly loaded petrol and diesel car engines.

Wolver Rally Special SAE 10W-60 is ideal for engines which are submitted to hardest conditions in motor sports. With its broad viscosity, SAE 10W-60 extremely high temperature stability can be assured.

Wolver Rally Special SAE 10W-60 fulfills the high quality requirements of all car producers.