Haibike ALLMTN 3



MTB Fully coffee/green/blue glossy 41



For the trails off the beaten track. Our ALLMTN 3 is an absolute all-rounder that can take on any terrain. The eFully comes with 160mm front and rear suspension travel, powerful four-piston disc brakes from Shimano and the powerful Yamaha PW-X3 drive – and is ready to experience all-mountain adventures at their best. Thanks to the mixed wheel sizes of 29"/27.5" and the wide Continental Kryptotal tyres, you always enjoy perfect traction and master even the steepest uphills and downhills without any problems – no matter how rough the terrain is. Practical: with the Modular Rail System, you can mount accessories such as bags or a bottle cage on the bike. This gives you maximum flexibility on your adventures – even when you're exploring trails off the beaten track.

€ 5199

Specification

Frame and more

Brand Haibike

Frame Haibike aluminium, 29"

Frame shape MTB Fully
Model name ALLMTN 3
Total perm. weight 135
Frame height 41

Fork RockShox 35 Gold RL DebonAir, Boost 160 mm

Damper RockShox Deluxe Select 205x65mm, Trunnion, DebonAir+

FSA NO.57-HBS/U-200 Anod Black 1-1/8"-1.5"

w/H2442+H2621

Propulsion

Head set

Drive unit Yamaha PW-X3, 250W, 25km/h, 85Nm

Charger Yamaha Standard Charger 4A
Battery Yamaha InTube 720Wh

Battery capacity 720

Display Yamaha A2 Display

Engine manufacturer Yamaha
Engine torque 85

Gear shift and brakes

Gear shift Shimano Deore RD-M6100 12s, Shadow+, 12 gears, Deore

SL-M6100, Rapidfire+, trigger switch

Chain Shimano M6100

Brakes Shimano Deore BR-MT420, 4 pistons, PM, 203mm

Brake lever Shimano BL-MT401, aluminium Chain guide Winning Nylon direct mount

Crank arm Samox ISIS Crankarm 160 mm (S+M) / 165 mm (L+XL)

Handlebar and saddle

Saddle Selle Royal Vivo

Handlebar Haibike TheBar++ Dia. 31.8 mm, 780 mm

Grips Velo VLG-1751D2, MTB Grips

Wheels and wheel components

Rims WTB ST i30 TCS 2.0 32H, eyeleted, Hollow section rim

Geometry

Seat tube length 410 Seat tube angle 75 Head tube length 120 Head tube angle 64.5 Chain stay length 460 Bottom bracket drop -20 421 Reach Seat tube offset 23