

ENERGOOSZCZĘDNA ŻARÓWKA LED

PAR16-AP



BRAK MIGOTANIA
FLICKER FREE



PAR16-AP GU10 5W

PAR16-AP GU10 6W

PAR16-AP GU10 7W

PAR16-AP GU10 8W

PAR16-AP GU10 9W

PAR16-AP GU10 10W

Dane techniczne:

	5 W	6 W	7 W	8 W	9 W	10 W
Moc	5 W	6 W	7 W	8 W	9 W	10 W
Strumień świetlny	470 lm	554 lm	638 lm	806 lm	1055 lm	1149 lm
Odpowiednik	40 W	45 W	50 W	60 W	75 W	80 W
Trzonek	GU10	GU10	GU10	GU10	GU10	GU10
Napięcie	220-240 V	220-240 V	220-240 V	220-240 V	175-265 V	175-265 V
Współczynnik DF	>0,5	>0,5	>0,5	>0,5	>0,5	>0,7
Typ diody	SMD 2835	SMD 2835	SMD 2835	SMD 2835	SMD 2835	SMD 2835
Kąt świecenia	120°	120°	120°	120°	120°	120°
Oddawanie barw	Ra>80	Ra>80	Ra>80	Ra>80	Ra>80	Ra>80
Ściemnialna	✗	✗	✗	✗	✗	✗
IC	✓	✓	✓	✓	✓	✓
Średnica	50 mm	50 mm	50 mm	50 mm	50 mm	50 mm
Wysokość	56 mm	56 mm	56 mm	56 mm	60 mm	60 mm
🔍 Nr artykułu	251090134	128969935	251090140	251090381	251090219	251090419
🔍 Nr artykułu	251090135	128969936	251090141	251090382	251090220	251090420
🔍 Nr artykułu	✗	✗	✗	✗	✗	✗

