

Eaton 216843

Catalog Number: 216843

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, maintained, 3 positions, White, Bezel: titanium

General specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Illuminated selector switch actuator	216843
	EAN
	4015081833283
Product Length/Depth	Product Height
46 mm	30 mm
Product Width	Product Weight
30 mm	.013 kg
Compliances	Certifications
CE Marked	UL 508
	EN 60947-5
	CSA Std. C22.2 No. 94-91
	CSA Std. C22.2 No. 14-05
	IEC 60947-5
	VDE
	UL File No.: E29184
	IEC/EN 60947-5
	VDE 0660
	CE
	CSA Class No.: 3211-03
	CSA-C22.2 No. 94-91
	UL Category Control No.: NKCR
	CSA
	CSA-C22.2 No. 14-05
	CSA File No.: 012528
	IEC/EN 60947
	UL
	DNV
	CI



Charakterystyka & Funkcje

Bezel color

Titanium

Bezel material

Plastic

Color

White

Design

With thumb-grip

Classical

Fitted with:

Front ring

Functions

Stay-put/spring-return function, can be changed with coding parts M22-XC-Y

Parametry ogólne

Accessories

Thumb grip

Degree of protection

NEMA 4X, 13

Degree of protection (front side)

IP66

Lifespan, mechanical

100,000 Operations

Opening diameter

22.5 mm

Operating frequency

2000 Operations/h

Operating torque

.3 Nm

Product category

RMQ-Titan

Size

Front diameter: 29.7 mm

Suitable for

Illumination

Switching angle

60 °

Type

Illuminated selector switch actuator

Warunki otoczenia, mechaniczne

Mounting position

As required

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal

Klimatyczne warunki środowiskowe

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

shock 11 ms

Komunikacja

Connection to SmartWire-DT

Yes

With SWD-RMQ connections

Słownik

Actuator color

Black

Actuator function

Maintained

Switching function latching

Actuator type

Toggle

Number of switch positions

3

Styki

Force for positive opening - min

0 N

Weryfikacja projektu

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdis

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Do pobrania

2D drawings

116X115

116X196

0000SPC-180

eaton-operating-button-symbol-013.eps

116C063

Modele 3D

DA-CS-wahltaste_knebel

DA-CD-wahltaste_knebel

Instruction/installation leaflet

IL04716002Z



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia