



Tabele doboru siłowników:

Siłowniki Mobilus M35:

początkowa średnica nawojowa [ mm ]		Φ 40 mm			Φ50 mm		
wysokość rolety [ m ]		1,5 m	2,5 m	3,0 m	1,5 m	2,5 m	3,0 m
[ Nm ]	[ rpm ]	[ kg ]	[ kg ]	[ kg ]	[ kg ]	[ kg ]	[ kg ]
5	14	10	8	6	8	6	3
6	28	10	8	6	8	6	3
10	14	19	17	14	17	15	12
13	14	28	26	23	26	24	21

Siłowniki Mobilus M45:

początkowa średnica nawojowa [ mm ]		Φ60 mm			Φ70 mm		
wysokość rolety [ m ]		1,5 m	2,5 m	3,0 m	1,5 m	2,5 m	3,0 m
[ Nm ]	[ rpm ]	[ kg ]	[ kg ]	[ kg ]	[ kg ]	[ kg ]	[ kg ]
10	17	18	15	12	15	12	8
15	17	30	26	22	26	23	20
25	17	50	40	35	45	40	30
35	13	75	65	55	65	55	45
50	12	95	80	70	80	70	60



[Technologia COSMO | 2WAY oraz lista urządzeń pracujących w tym standardzie](#)



[Katalog produktów Mobilus](#)