

Power Kit Details			Cable Length				Supplied Fuse Rating	Max Fuse-Holder Capacity
			< 1.5m	1.5 > 3m	3m > 4m	4m > 5m		
GT-PK10	10 AWG	Max Continuous Current (Cable@Length)	140A	70A	46A	36A	60A	150A
		Max Amplifier RMS Watts Assuming 70% Efficiency	1176w	588w	386w	302w		
GT-PK8	8 AWG	Max Continuous Current (Cable@Length)	175A	87A	58A	45A	80A	150A
		Max Amplifier RMS Watts Assuming 70% Efficiency	1470w	731w	487w	378w		
GT-PK4	4 AWG	Max Continuous Current (Cable@Length)	442A	222A	149A	112A	100A	150A
		Max Amplifier RMS Watts Assuming 70% Efficiency	3713w	1865w	1252w	941w		
VOLT/8	8 AWG	Max Continuous Current (Cable@Length)	215A	100A	67A	55A	80A	150A
		Max Amplifier RMS Watts Assuming 70% Efficiency	1806w	840w	563w	462w		
VOLT/4	4 AWG	Max Continuous Current (Cable@Length)	512A	251A	171A	145A	100A	150A
		Max Amplifier RMS Watts Assuming 70% Efficiency	4301w	2108w	1436w	1218w		
VOLT/0	0 AWG	Max Continuous Current (Cable@Length)	1345A	669A	445A	320A	150A	300A
		Max Amplifier RMS Watts Assuming 70% Efficiency	11298w	5620w	3738w	2688w		