



## Supertec 5W-40

### SPECIFICATIONS

Engine:	gasoline, diesel
SAE:	5W-40
API:	SN / CF
ACEA:	A3/B4

### APPROVALS AND CONFORMITY

MB 229.3

MB 229.5   VW 502.00   VW 505.00   VW 501.01   PSA B71 2296   PSA B71 2300   BMW Longlife-01

RENAULT RN0700   RENAULT RN0710   OPEL GM-LL-B025   Porsche A40

### CHARACTERISTICS

- Extrem wear protection;
- Excellent viscosity-temperature behavior;
- Minimal frictional loss;
- Very high cleaning capability;
- Low volatilization loss;
- High oxydation- and thermo stability.

### EFFECTS

- Reduces fuel consumption according API EC and reduces exhaust emission;
- Excellent cold starting properties - rapid supply of all points of lubrication;
- Very good operating reliability;
- Optimal engine cleanliness;
- Lowst oil consumption;
- High margin of performance and high product stability;
- Extended oil change intervals;
- Prevents black sludge formation;
- All-year operation.

### DISPOSAL

- Wolver Supertec SAE 5W-40 is assigned to category 2 of used oils and thus is free for disposal.

TYPICALS

Kinematic viscosity at 100 °C	14.3 mm²/s
Viscosity index	171
Pour point	-35 °C
Viscosity CCS at -30 °C	4800 mPa·s
TBN	9.2 mgKOH/g
Flash point	216 °C
Density at 15.6 °C	847 kg/m³

DESCRIPTION

Wolver Supertec SAE 5W-40 is a hightec HC-Synthetic lightrun motor oil especially developed for heavily stressed petrol and diesel car motors.

Wolver Supertec SAE 5W-40 meets the manufacturers high quality demands for cars. It is excellently applicable for long oil changing intervals and for motors with direct injection. Ideal for hard use at motorways and over short distances.

Utilization

- High-performance and normal four-stroke petrol engines;
- with multivalve technology;
- with turbocharging;
- with catalyst technology;
- Passenger car diesel engines;
- Suction diesel;
- Turbo diesel;
- with CDi-technology;
- Direct-injection.

Miscibility

Wolver Supertec SAE 5W-40 is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of Wolver Supertec SAE 5W-40 it is recommendable to use only Wolver Supertec SAE 5W-40 when refilling.

1L - Can	4107	4260360941078
4L - Can	4001	4260360940019
20L - Pail	4060	4260360940606
60L - Barrel	4190	4260360941900

---

208L - Barrel	4030	4260360940309
---------------	------	---------------

---