



**BORMA WACHS**<sup>®</sup>  
Wood Professional Cosmetics



## Technical Data Sheet

REV 00 of 20.10.2012

# GRUNDIEROIL COLOROIL

## Color Oil Basecoat

### DESCRIPTION:

Mixture of oils and resins, specially formulated for the correct first hand application on any oil finishing treatment. Ready for use, it protects efficiently and for a long time every kind of raw wood surface. Penetrating deeply, it adheres to wood, giving a correct first hand protection. Thanks to the addition of UV filters and other additives for the protection against harmful agents, it guarantees an excellent protection for longlasting finishing cycles, for exterior suggested with Holzwachs Lasur or Decking Oil, for interiors Parquet Oil range.

### PHYSICAL – CHEMICAL CHARACTERISTICS:

<b>Appearance :</b>	liquid
<b>Colour :</b>	Clear, White, Wenge, Natural Oak, Grey Oak, Olive Green, Cherry
<b>Odour :</b>	odourless
<b>Yield:</b>	8/12 m <sup>2</sup> /L
<b>Dilution:</b>	Solvoil 04

### METHOD OF USAGE:

After the application of Borma fillers to remove superficial defects, apply the product directly by spray or brush on a surface free from grease, oil and wax. Apply one coat or more, waiting from 4 to 6 hours between consecutive treatments. After complete drying, usually from 8 to 12 hours, the support can be finished with further treatments, e.g. for indoor use with Borma Parquet Oil range and for outdoor use with Decking Oil.

Warning: the product is overpaintable. If overpainting is necessary, please verify compatibility between products.

### PACKAGE:

The product comes in Lt 1, Lt 5, Lt 10 and Lt 20 sized cans.



**BORMA WACHS**<sup>®</sup>

Wood Professional Cosmetics

**STORAGE:**

Store in a cool, well ventilated place, keep the container close when not in use. Keep away from heat, flames, sparks and other sources of ignition. Shelf life of the product is 12 months.

**FOREWORD:**

Sawdust, cotton cloth, paper and similar products soaked with liquid product and let in such condition may cause spontaneous combustion. Therefore, in case of presence of these materials for cleaning, ensure adequate air ventilation of the rooms in order to allow a rapid drying of the product or wet them with water before disposal.

Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.