



## UB200C-B

Article number: 138-00046



### Certifications & Approvals

RoHS

### Base Data

|                                                     |                              |  |
|-----------------------------------------------------|------------------------------|--|
|                                                     |                              |  |
| Colour                                              | Black (BK)                   |  |
| Description Short (BMEcat)<br>(max. 150 characters) | Cable Tie PA66 200x4.6 black |  |
| Fixation Method                                     | None                         |  |
| GLOBAL PART NAME (auto<br>set)                      | UB200C-B-PA66-BK             |  |
| Identification Plate Position                       | none                         |  |
| Pack Cont.                                          | 100 pcs.                     |  |
| Package Quantity per                                | bag                          |  |
| Releasable Closure (Yes/No)                         | No                           |  |
| Tie Closure                                         | plastic pawl                 |  |
| Variant                                             | Inside Serrated              |  |

### Product Dimensions

|            |          |  |
|------------|----------|--|
|            |          |  |
| Length (L) | 200.0 mm |  |

Contact

|           |        |
|-----------|--------|
| Width (W) | 4.6 mm |
|-----------|--------|

## Material and Specifications



|                               |                                                                                   |
|-------------------------------|-----------------------------------------------------------------------------------|
| ELV compliant (Article 4 - 2) | YES                                                                               |
| Hazardous goods               | No                                                                                |
| Material                      | Polyamide 6.6 (PA66)                                                              |
| Operating Temperature - °C    | -40 °C to +85 °C                                                                  |
| Specifications                |  |

## Logistics and Packaging



## More Information



|          |          |
|----------|----------|
| ETIM 5.0 | EC000046 |
| ETIM 6.0 | EC000046 |

Update: 18/12/2017

© HellermannTyton 2017

Contact 