

OWNER'S MANUAL - PRODUCT FICHE

RELATED OWNER'S MANUAL CODE: **16122000A67139**

Trade Mark	Rotenso			
Indoor Model	RO26Xi R14	RO35Xi R14	RO50Xi R14	RO70Xi R14
Outdoor Model	RO26Xo R14	RO35Xo R14	RO50Xo R14	RO70Xo R14
Sound Power Level at Standard Rating Conditions(Indoor/Outdoor)[dB(A)]	58/64	59/65	59/65	65/68
Refrigerant Type	R32	R32	R32	R32
GWP	675	675	675	675
Charge amount (g)	690	690	1100	1500
CO2 equivalent (tonnes)	0.465	0.465	0.74	1.01
SEER	8.6	8.5	8.5	8.5
Energy efficiency Class in cooling	A+++	A+++	A+++	A+++
Annual Electricity Consumption in Cooling[KWh/y] [1]	106	144	220	288
Design Load in cooling Mode (Pdesign)[KW]	2.6	3.5	5.3	7.0
SCOP (average heating season)	4.6	4.6	4.3	4.2
Energy efficiency class in heating (average season)	A++	A++	A+	A+
Annual electricity consumption in heating (average season)[KWh/y][2]	731	731	1400	1666
Warmer heating season	Y	Y	Y	Y
Colder heating season	—	—	—	—
Design load in heating mode (Pdesign)[KW]	2.4	2.4	4.3	5.0
Declared capacity at reference design condition (heating average season)[KW]	1.920	1.926	3.646	4.181
Back up heating capacity at reference design condition (heating average season)[KW]	0.480	0.474	0.654	0.819

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional

Contains fluorinated greenhouse gases.

Importer: THERMOSILESIA, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland

Manufacturer: ROTENSO, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland

[1] [2] Energy consumption "XYZ" kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Note: Please check the model information above according to the model name on the nameplate.

KARTA PRODUKTU				
KOD KARTY PRODUKTU: 16122000A67139				
Znak towarowy	Rotenso			
Jednostka wewnętrzna	RO26Xi R14	RO35Xi R14	RO50Xi R14	RO70Xi R14
Jednostka zewnętrzna	RO26Xo R14	RO35Xo R14	RO50Xo R14	RO70Xo R14
Poziom mocy akustycznej (jednostka wewnętrzna/jednostka zewnętrzna [dB(A)])	58/64	59/65	59/65	65/68
Rodzaj czynnika chłodniczego	R32	R32	R32	R32
GWP	675	675	675	675
Ilość czynnika chłodniczego (g)	690	690	1100	1500
Ekwiwalent CO2 (tCO2eq)	0.465	0.465	0.74	1.01
SEER	8.6	8.5	8.5	8.5
Klasa efektywności - chłodzenie	A+++	A+++	A+++	A+++
Roczne zużycie energii elektrycznej - funkcja chłodzenia [KWh/y] [1]	106	144	220	288
Obciążenie chłodnicze [KW]	2.6	3.5	5.3	7.0
SCOP	4.6	4.6	4.3	4.2
Klasa efektywności - grzanie	A++	A++	A+	A+
Roczne zużycie energii elektrycznej - funkcja grzania [KWh/y] [2]	731	731	1400	1666
Sezon grzewczy cieplejszy	Y	Y	Y	Y
Sezon grzewczy chłodniejszy	_____	_____	_____	_____
Obciążenie grzewcze [KW]	2.4	2.4	4.3	5.0
Deklarowana wydajność w warunkach ogrzewania (średni sezon) [KW]	1.920	1.926	3.646	4.181
Zapas mocy w warunkach ogrzewania (średni sezon) [KW]	0.480	0.474	0.654	0.819
Wycieki czynników chłodniczych przyczyniają się do zmiany klimatu. W przypadku przedostania się do atmosfery czynnika chłodniczego o niższym współczynniku ocieplenia globalnego (GWP) ma mniejszy wpływ na globalne ocieplenie niż czynnik o wyższym współczynniku GWP. Urządzenie zawiera płyn chłodniczy o współczynniku GWP wynoszącym [675]. Powyższe oznacza, iż w przypadku przedostania się 1 kg takiego płynu chłodniczego do atmosfery, jego wpływ na globalne ocieplenie byłby [675] razy większy niż wpływ 1 kg CO2 w okresie 100 lat. Nigdy nie należy samodzielnie manipulować przy obiegu czynnika lub demontować urządzeń, należy zawsze zwrócić się o pomoc do specjalisty.				
Zawiera fluorowane gazy cieplarniane.				
Importer: THERMOSILESIA, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland				
Manufacturer: ROTENSO, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland				
[1] [2] Zużycie energii „XYZ” kWh na rok, oparte na standardowych wynikach testu. Rzeczywiste zużycie energii zależy od sposobu użytkowania urządzenia i jego umiejscowienia.				
Uwaga: Proszę sprawdzić powyższe informacje o urządzeniu czy zgadzają się z nazwą modelu na tabliczce znamionowej.				

OWNER'S MANUAL - PRODUCT FICHE					
RELATED OWNER'S MANUAL CODE: CS014UI-EP(C)					
Trade Mark		Rotenso			
Model: Indoor		RO26Xi R14	RO35Xi R14	RO50Xi R14	RO70Xi R14
Model: Outdoor		RO26Xo R14	RO35Xo R14	RO50Xo R14	RO70Xo R14
Sound power level at standard rating conditions (Indoor/Outdoor) [dB(A)]		58/64	59/65	59/65	65/68
Refrigerant type		R32	R32	R32	R32
GWP ^[1]		675	675	675	675
Charge amount ^[1] [g]		690	690	1100	1500
CO2 equivalent ^[1] [tonnes]		0.465	0.465	0.74	1.01
SEER [W/W]		8.6	8.5	8.5	8.5
Energy efficiency class in cooling		A+++	A+++	A+++	A+++
Annual electricity consumption in cooling ^[2] [kWh/a]		106	144	220	288
Design load in cooling mode (Pdesign) [kW]		2.6	3.5	5.3	7.0
SCOP (average heating season) [W/W]		4.6	4.6	4.3	4.2
Energy efficiency class in heating (average season)		A++	A++	A+	A+
Annual electricity consumption in heating (average season) ^[2] [kWh/a]		730	730	1400	1666
Design load in heating mode (Pdesign) [kW]		2.4	2.4	4.3	5.0
Declared capacity at reference design condition (Average) [kW]		1.920	1.926	3.646	4.181
Back up heating capacity at reference design condition (Average) [kW]		0.480	0.474	0.654	0.819
SCOP (Warmer) [W/W]		5.1	5.1	5.4	5.3
Energy efficiency class in heating (Warmer)		A+++	A+++	A+++	A+++
Annual electricity consumption in heating (Warmer) ^[2] [kWh/a]		660	686	1118	1453
Design load in heating mode (Pdesign) (Warmer) [kW]		2.4	2.5	4.3	5.5
Declared capacity at reference design condition (Warmer) [kW]		2.400	2.500	4.300	5.500
Back up heating capacity at reference design condition (Warmer) [kW]		0.000	0.000	0.000	0.000
SCOP (Colder) [W/W]		3.8	3.8	3.6	3.3
Energy efficiency class in heating (Colder)		A	A	A	B
Annual electricity consumption in heating (Colder) ^[2] [kWh/a]		1989	2043	3733	4645
Design load in heating mode (Pdesign) (Colder) [kW]		3.6	3.6	6.4	7.3
Declared capacity at reference design condition (Colder) [kW]		2.130	0.861	2.969	3.376
Back up heating capacity at reference design condition (Colder) [kW]		1.500	2.700	3.400	3.900
[1] Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [675]. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [675] times higher than 1kg of CO2 , over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional					
Contains fluorinated greenhouse gases.					
Importer: THERMOSILESIA, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland					
Manufacturer: ROTENSO, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland					
[2] Energy consumption "XYZ" kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.					

Note: Please check the model information above according to the model name on the nameplate.