Sensor-switched outdoor light

L 30 S

with motion detector EAN 4007841 068899 Article number 068899













Max. Radius 10 m







2 - 2000 Lux

Subject to technical modifications









Max. 60 W E27

Function description

Modern, anthracite-coloured L 30 S outdoor luminaire for attractive ambient lighting around the house. Designed for E27 light bulbs. With swivelling 180° infrared sensor and adjustable follow-up time (8 seconds to 35 minutes). Body made of UV-resistant plastic. Ideal mounting height: 2 m. Also available without sensor.

Technical specifications

| Dimensions (L x W x H) | 108 x 122 x 261 mm |
|---|---|
| With lamp | No |
| Manufacturer's Warranty | 3 years |
| Settings via | Potentiometers |
| With remote control | No |
| Version | with motion detector |
| PU1, EAN | 4007841068899 |
| Application, place | Outdoors |
| Application, room | garden, front door, courtyard & driveway, all round the building, terrace / balcony |
| Colour | Anthracite |
| includes sheet of self-adhesive numbers | No |
| Installation site | wall |
| Impact resistance | IK07 |
| IP-rating | IP44 |
| Protection class | II |
| | |

| Output | 15 W |
|---|--------------------------------------|
| Mounting height max. | 3,00 m |
| Sneak-by guard | No |
| Capability of masking out individual segments | No |
| Electronic scalability | No |
| Mechanical scalability | No |
| Reach, radial | $r = 3 \text{ m} (14 \text{ m}^2)$ |
| Reach, tangential | $r = 10 \text{ m} (157 \text{ m}^2)$ |
| Photo-cell controller | Yes |
| Abdeckmaterial Lieferumfang | sticker |
| Base | E27 |
| Soft light start | No |
| Twilight setting | 2 – 2000 lx |
| Time setting | 8 s – 35 Min. |
| Basic light level function | No |
| Twilight setting TEACH | No |

Sensor-switched outdoor light

L 30 S

with motion detector EAN 4007841 068899 Article number 068899




Technical specifications

| Ambient temperature | -20 - 40 °C |
|---------------------|--------------------------|
| Housing material | Plastic |
| Cover material | Plastic, opal |
| Mains power supply | 220 – 240 V / 50 – 60 Hz |

| Interconnection | No |
|-------------------------|-------|
| Optimum mounting height | 2 m |
| Detection angle | 180 ° |

Dimension Drawing



Circuit diagram

