



Ledinaire All-in floodlights

BVP167 LED84/830_40_65 PSU 70W SWB

Ledinaire All-in floodlights, 70 W, 7700 lm, 8400 lm, 3000 K, 4000 K, 6500 K, CRI80, Symmetrical, IP65

With this Ledinaire all-in floodlights range, you can easily adjust the color temperature by a simple switch. No need to choose between warm white, neutral white or cool white anymore, you get all this in one single product ! The range comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General Information		Operating and Electrical	
Lamp family code	LED84S [LED Module, system flux 8400 lm]	Luminous Efficacy (rated) (Nom)	120 110 lm/W
Number of gear units	1 unit	Color rendering index (CRI)	>80
Driver included	Yes	Light source color	Multi Color Temperature
Light source engine type	LED system in flux	Optic type	Symmetric 110°
Value ladder	Value	Luminaire light beam spread	110°
Serviceability class	Class C, luminaire without serviceable parts, not serviceable	Optic type outdoor	Symmetrical
Warranty period	3 years	All-in Type	All-in, Multi Color Temperature
Sustainability rating	-	Effective projected area	0.037625 m²
Light Technical			
Upward light output ratio	0	Input Voltage	220-240 V
Luminous Flux	7,700 8,400 lm	Line Frequency	50 or 60 Hz
Correlated Color Temperature (Nom)	3000 4000 6500 K	Inrush current	3.64 A
		Inrush time	0.0222 ms
		Power Consumption	70 W
		Power Factor (Fraction)	0.95

Ledinaire All-in floodlights

Connection	Flying leads/wires
Cable	Cable 2.0 m without plug
Number of products on MCB of 16 A type B	31
Suitable for random switching	Not applicable
Protection class IEC	Safety class I
Surge Protection (Common/Differential)	Surge protection level until 1.5 kV differential mode and 1.5 kV common mode
Total harmonic distortion	20 %

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Driver integrated on LED board (DoB)
Constant light output	No
Embedded control	-
Photocell	-

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover material	Tempered glass
Fixation material	Steel
Housing Color	Grey
Mounting device	Via U Shaped Bracket, Aiming Scale Angle, Universal Installation
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	286 mm
Overall width	203 mm
Overall height	33 mm
Dimensions (Height x Width x Depth)	33 x 203 x 286 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Standard tilt angle posttop	27°
Standard tilt angle side entry	-
Optical cover type	Glass
Net Weight (Piece)	1.364 kg

Emergency Operation

Central Emergency	No
-------------------	----

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Ambient temperature range	-25 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.440,0.403); (0.369,0.364); (0.313,0.337) SDCM<5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	-2
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM<5

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L80

Product Data

Order product name	BVP167 LED84/830_40_65 PSU 70W SWB
Full product name	BVP167 LED84/830_40_65 PSU 70W SWB
Full product code	872016973605499
Order code	911401875386
Material Nr. (12NC)	911401875386
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169736054
Numerator - Packs per outer box	10
EAN/UPC - Case	8720169736245

Ledinaire All-in floodlights

Dimensional drawing

