# Haibike ALLMTN 2

# High pebble/black/red matt 44





Whether tricky root passages, flowing trails or crisp climbs, our ALLMTN 2 is your ticket to the world of unlimited all-mountain possibilities. A bike for which all paths are open to you. This is ensured not least by the mountain-savvy all-round equipment: thanks to 160mm travel at the fork and rear, plus a wheel mix of 29" front and 27.5" rear, you can roll over any obstacle in a relaxed manner on the downhills and still enjoy perfect traction on steep uphills. The compact and powerful Yamaha PW-X3 motor pushes you up even the steepest climbs in no time, while the 720Wh battery ensures that you can make the most of the electric tailwind even on long tours. In short: with this eMountainbike you will experience extreme off-road fun – regardless of how demanding the terrain is.

€ 4999

# Specification

### Frame and more

Brand Haibike

Frame Haibike aluminium, 29"

Frame shape Model name
ALLMTN 2 Total perm. weight
120 Frame height

44 Fork
RockShox 35 Gold RL DebonAir, Boost 160 mm Damper
RockShox Deluxe Select 205x65mm, Trunnion, DebonAir+ Head set

FSA NO.57-HBS/U-200 Anod Black 1-1/8"-1.5"

w/H2442+H2621

# **Propulsion**

Drive unit Yamaha PW-X3, 250W, 25km/h, 85Nm

Charger Yamaha Standard Charger 4A
Battery Yamaha InTube 720Wh

Battery capacity 720

Display Yamaha A2 Display

Engine manufacturer Yamaha Engine torque 85

## Gear shift and brakes

Gear shift Sram SX Eagle 12s, 12 gears, SX Eagle Single Click Trigger,

trigger switch

Chain Sram SX Eagle 12s

Brakes Tektro TRP Slate EVO HD-M807, 4 pistons, 203 mm

Brake lever Tektro TRP Slate EVO HD-M807-BL

Derailleur hanger Sram UDH

Chain guide Winning Nylon direct mount

Crank arm Samox ISIS Crankarm 160 mm (S+M) / 165 mm (L+XL)

# Handlebar and saddle

Saddle Selle Royal Vivo

Handlebar Haibike Components TheBar ++, 780 mm

Grips XLC VLG-1751D2, MTB Grips

### Wheels and wheel components

Rims WTB ST i30 TCS 2.0 32H, eyeleted, Hollow section rim

## Geometry

Seat tube length	440
Seat tube angle	75
Head tube length	120
Head tube angle	64.5
Chain stay length	460
Bottom bracket drop	-20
Reach	451
Seat tube offset	23