

LogiLink_®

USB-C GaN Wall Charger 20 W

Art. No.: **PA0345 PA0346**



GaN chargers are physically smaller, and conduct higher voltages than silicon-based chargers with better heat dissipation. Charge smartphones, tablets or laptops at full speed with 20 W USB-C Power Delivery at home, in the office or on-the-go.

















Ultra-slim design, easy to carry and takes up less space.



Up to 20 W output for a variety of devices from tablets to smartphones; it powers your devices at incredible speeds.



Extremely safe, comes with overcurrent, overvoltage, overheating, overcharge, overload and short circuit protections.



Widely compatible with most USB devices such as smartphones, tablets and much more.



Specification:





3.3-11 V/1.8 A (20 W)

Art. No.	PA0345	PA0346	
Power Output Interface	1 x USB-C female	1 x USB-C female + 1 x USB-A female	
Input	100–240 V∼, 50/60 Hz, max. 0.6 A	100–240 V~, 50/60 Hz, max. 0.6 A	
Output	USB-C PD 3.0: 5 V/3 A (15 W), 9 V/2.22 A (20 W), 12 V/1.67 A (20 W) Total output: 20 W max.	USB-C PD 3.0: 5 V/3 A (15 W), 9 V/2.22 A (20 W), 12 V/1.67 A (20 W) USB-A QC 3.0: 5 V/3 A (15 W), 9 V/2 A (18 W), 12 V/1.5 A (18 W) USB-A + USB-C: 5 V/3 A (15 W) PPS: 3.3–5.9 V/3 A (20 W)	

Efficiency Level VI
Operating Temperature -10–35°C

Operating Humidity 20–80% RH (non-condensing)

Color White

Dimensions 8.1 x 3.6 x 1.5 cm

Weight 37.5 g

⁽¹⁾ Proper use of the PD function can only be guaranteed in combination with certified USB cables with E-Mark chipset.



- Package Contents:
 » 1x USB-C Wall Charger
- » 1x User Manual

Package Information:

Art-No.	Packing Dimension	Packing Weight	Carton Dimension	Carton Q'ty	Carton Weight
PA0345	75 x 25 x 95 mm	0.059 kg	290 x 210 x 400 mm	100 pcs	6.2 kg
PA0346	75 x 25 x 95 mm	0.059 kg	290 x 210 x 400 mm	100 pcs	6.27 kg

