

SCART to HDMI Converter

User Manual

Thank you for choosing our products. We focus on producing professional, high-quality, cost-effective high-tech products, So you can easily enjoy high-definition digital life brought by technology.

For the optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting the product. And please keep this manual for future reference.

Introduction:

This SCART To HDMI converter is a universal converter for analog SCART input to HDMI 1080p (60HZ) output. It can connect the playback device only has SCART interface such as DVD, Set-top box to the HD display device. The analog to digital conversion in this module employs 10 bits maximal 162MSPS sampling, black/white level expansion, color transition improvement, dynamic range expansion, blue stretch, auto-detect and auto-convert the composite signal to 1080p(60Hz) output Making video come alive, delivering the sharpest, most realistic HD visuals.

Features:

- No need to install drivers, portable, flexible, plug and play
- Provide advanced signal processing to ensure great precision, colors, resolutions, and details.
- Support PAL, NTSC3.58, NTSC4.43, SECAM, PAL/M, PAL/N standard TV formats input.
- Support HDMI 1080p or 720p output.

Specifications:

SCART Input..... PAL, NTSC3.58, NTSC4.43 SECAM, PAL/M, PAL/N

HDMI Output..... 1080p/720p

HDMI Output Cable Distance ≤7m AWG26 HDMI Standard Cable

SCART Input Cable Distance ≤8m AWG26 SCART Standard Cable

Max Working Current..... 350mA

Power Adapter Format..... AC 100V-240V 50/60HZ, DC 5V/1A

Operating Temperature Range..... -10~+55℃

Storage Temperature Range..... -20~+60℃

Operating Humidity Range..... 10~90%RH (No Condensation)

Storage Humidity Range..... 5~95%RH (No Condensation)

Case Dimension..... 88.5*57.5*25 (mm)

Weight..... 60g

Operation controls and Functions:




SCART Input: Use a SCART to SCART cable to connect your SCART device to this converter. Such like DVD, Sky Box, STB, etc.

DC/5V: Connect power adapter or use the USB power cable to connect the converter to the computer's USB, TV's USB or your 5V USB charger, etc.

Power: When the DC5V power on, this indicator will be light.

HDMI Output: Use a "HDMI to HDMI cable" to connect this converter to your TV which has a HDMI input interface.

Connection Diagram:



Package Contents:

SCART to HDMI Converter 1pcs

DC5V/1A Power Adapter or USB cable 1pcs

User Manual 1pcs

Note:

- Please correctly use and keep the converter to guarantee the product performance and work as expected.
1. Please do not expose this unit to the damp, high-temperature, dusty, erosive, or oxidative environment.
 2. All parts will be free from the strong shake, hit fall.
 3. Please do not touch the item with wet hands.
 4. Please hold the plug when unplugging. Do not pull the power cable directly.
 5. Please turn the unit off when it is not in use for a long period of time.
 6. Please do not open the cover and do not touch the inside parts.
 7. Please use the original factory power adapter.

FAQ:

Before switching on the extractor, please check all the cables carefully and make sure all the interfaces are connected correctly. The common problems and the relevant solutions are showed as follows.

No	Problem Description	Solutions
1	Non-Power-Connected	Check if the power adapter plug is truly and correctly inserted the power socket and the power switch is turned on.
2	No Sound/Abnormal Sound	1. Confirm the sound channels and the interfaces are well connected. 2. Confirm the input audio format is supported format. 3. Confirm the amplifier /TV set volume is not be muted.
3	No Picture/Abnormal Picture	1. Please make sure the signal source and the TV are turned on and connected to the item correctly. 2. Check whether the signal source output resolution has been set too high. 3. Device EDID read error, please reboot. 4. Please use high quality HDMI cable.