

FPV camera Pilotix P6 Pro





- * Image is for reference only
- Good night vision, low illumination up to F1.2/0.01LUX
- Low latency
- Ultra-wide input voltage from 5-40V
- With WDR, you can see your surroundings in complex environments

Product Specification			
Product name	FPV camera Pilotix P6 Pro		
Model	P6 Pro		
SKU	6577		
Electrical parameters			
Analog video	CVBS		
Operating voltage	5V-40V		
Operating current	130mA@12V		
Physical Properties			
Weight	9g		
Dimensions (L × W × H)	29.7mm × 19mm × 19mm		
Mounting hole diameter	M2		
Overview			
Sensor	Sony 1/3" CMOS		
Horizontal resolution	1800TVL		
Pixel dot size	3.75µm		
Picture ratio	16:9 4:3 Optional		
Video format	PAL/NTSC Switchable		
Field of view	FOV : H 100° V70°		
Low illumination	F1.2/0.01Lux		
Operating temperature	-20°C - 70°C		
Operating temperature Image Adjustments			
Image Adjustments	-20°C - 70°C		
Image Adjustments Electronic shutter White balance Noise reduction	-20°C - 70°C Auto Auto 3D		
Image Adjustments Electronic shutter White balance	-20°C - 70°C Auto Auto		

Package includes

- x1 FPV camera Pilotix P6 Pro
- x1 Video signal cable (90mm length)
- x1 OSD cable (90mm length)
- x2 M2*4mm
- x2 M2*2mm

Note:

Pin Definitions:

1	POWER	DC5 - 40V
2	GND	-
3	CVBS	CVBS video signal
4	OSD	
5	OSD	





Make sure the pin assignments on your flight controller match the required connections.