



Multihog

www.multihog.com

Multihog MH90 Technical Specifications	
<u>Dimensions/Weights</u>	
Length	3400mm
Width	1855mm
Height	2400mm
Wheel Base	1760mm
Unladen Weight	2800kg
Max Front Axle Weight	4000kg
Max Rear Axle Weight	4000kg
Unladen Weight	2800kg
Gross Laden Weight	6500kg
Turning Circle	2800mm
<u>Engine</u>	
Maker	Yanmar
Power	87.5HP
Emissions	Tier 3 Interim Tier 4
<u>Power Train</u>	
Drive	4 Wheel drive with 2 stage differential lock
Transmission	2 Speed heavy duty Hydrostatic Drive
Drive Controls	Full Automotive control for normal drive Fixed engine speed variable travel speed when operating an implement
Parking Brake	Automatic Multidisc Parking brake on rear wheels
<u>Steering</u>	
Type	Hydrostatic Power Steering
<u>Power Take Off/Hydraulic Functions</u>	
PTO	Hydraulic front and rear PTO
Flow	100 litres Front and Rear
Operating Pressure	250 Bar
Front Hydraulic Functions	1 Double Acting Section, 1 Double Acting Section with Float, 2 Single Acting Sections
Rear Hydraulic Functions	1 Double Acting Section, 1 Double Acting Section with Float, 2 Single Acting Sections
Operating pressure	220 Bar
Flow	30 Litres
Control	Single Multi-function Joystick Control
<u>Standard Equipment</u>	
Road Lights	Work Lights front and rear
Warning Beacon	Rear View Mirrors
Trailer Hitch	Air Suspension Drivers Seat
Adjustable Steering Column	Radio/CD/Aux
<u>Tyres</u>	
Standard – General Purpose	31.5 x 15.5 x 15
Tractor Grip Agricultural tyre	280/70 R16
Turf Tyre	33 x 16.5 x 15
Dual Tyres	31.5 x 15.5 x 15 + 6.50-15
Multihog have a policy of continuous improvement. These specifications may change without prior notice	