



## Eaton 248433

Eaton Distribution parts. Auxiliary contact, 1N/O+1N/C, 4A, 250V AC

### General specifications

|                      |                          |
|----------------------|--------------------------|
| PRODUCT NAME         | Eaton Distribution parts |
| CATALOG NUMBER       | 248433                   |
| EAN                  | 4015082484330            |
| PRODUCT LENGTH/DEPTH | 80 mm                    |
| PRODUCT HEIGHT       | 75 mm                    |
| PRODUCT WIDTH        | 8.8 mm                   |
| PRODUCT WEIGHT       | 0.038 kg                 |
| COMPLIANCES          | RoHS conform             |
| CERTIFICATIONS       | EN45545-2<br>IEC 61373   |
| MODEL CODE           | Z-AHK                    |

## Specyfikacje produktu

|                                               |                                                                                                                                                                                                                                     |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USED WITH                                     | Auxiliary contacts                                                                                                                                                                                                                  |
|                                               | Accessory for combined residual current/power circuit breaker                                                                                                                                                                       |
|                                               | Accessory                                                                                                                                                                                                                           |
|                                               | Accessory for miniature circuit breaker                                                                                                                                                                                             |
|                                               | Accessory for residual current circuit breaker                                                                                                                                                                                      |
| ACCESSORY/SPARE PART TYPE                     | Auxiliary contacts                                                                                                                                                                                                                  |
| MOUNTING METHOD                               | For fitting on left to: LS, FI/LS                                                                                                                                                                                                   |
| ADDITIONAL EQUIPMENT REQUIRED                 | Auxiliary switch                                                                                                                                                                                                                    |
| AMBIENT OPERATING TEMPERATURE - MAX           | 55 °C                                                                                                                                                                                                                               |
| AMBIENT OPERATING TEMPERATURE - MIN           | -5 °C                                                                                                                                                                                                                               |
| ASSEMBLY WIDTH                                | 0.5 TE                                                                                                                                                                                                                              |
| NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)     | 0                                                                                                                                                                                                                                   |
| NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS) | 1                                                                                                                                                                                                                                   |
| NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)   | 1                                                                                                                                                                                                                                   |
| NUMBER OF POLES AT MAIN CONTACT UNIT - MAX    | 2                                                                                                                                                                                                                                   |
| NUMBER OF SWITCHES (FAULT SIGNAL)             | 0                                                                                                                                                                                                                                   |
| VOLTAGE TYPE                                  | AC                                                                                                                                                                                                                                  |
| FUNCTIONS                                     | Auxiliary switch                                                                                                                                                                                                                    |
| DEVICE FITTING                                | Universal                                                                                                                                                                                                                           |
| TYPE                                          | <ul style="list-style-type: none"> <li>• Accessory</li> <li>• Accessory for combined residual current/power circuit breaker</li> <li>• Accessory for miniature circuit breaker</li> <li>• Accessory for residual current</li> </ul> |

## Do pobrania

|                      |                                              |
|----------------------|----------------------------------------------|
| DEKLARACJE ZGODNOŚCI | <a href="#">DA-DC-03 Z-AHK</a>               |
| INSTRUKCJE MONTAŻU   | <a href="#">MA150501253</a>                  |
| MODELE ECAD          | <a href="#">ETN.Z-AHK.edz</a>                |
| MODELE MCAD          | <a href="#">z_ahk.dwg z_ahk.stp</a>          |
| RYSUNKI              | <a href="#">eaton-dimensions-mas-ahk.jpg</a> |
| SCHEMATY POŁĄCZEŃ    | <a href="#">AHK</a>                          |

|                                                 |                                                                |
|-------------------------------------------------|----------------------------------------------------------------|
| circuit breaker                                 |                                                                |
| APPLICATION                                     | Switchgear for industrial and advanced commercial applications |
| RATED OPERATIONAL VOLTAGE (UE) - MAX            | 230 V                                                          |
| RATED SWITCH CURRENT                            | 3 A                                                            |
| SUITABLE FOR CURRENT OF MAIN CONTACT UNIT - MAX | 4 A                                                            |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATA:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Irelandia  
Eaton.com

Follow us on social media to get the latest product and support information.

