


P-CHANNEL ENHANCEMENT MODE VERTICAL DMOS FET

ISSUE 2 – SEPT 93

FEATURES

- * 45 Volt V_{DS}
- * $R_{DS(on)}=14\Omega$

BS250P



REFER TO ZVP2106A FOR GRAPHS

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Drain-Source Voltage	V_{DS}	-45	V
Continuous Drain Current at $T_{amb}=25^\circ C$	I_D	-230	mA
Pulsed Drain Current	I_{DM}	-3	A
Gate-Source Voltage	V_{GS}	± 20	V
Power Dissipation at $T_{amb}=25^\circ C$	P_{tot}	700	mW
Operating and Storage Temperature Range	T_j-T_{stg}	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Drain-Source Breakdown Voltage	BV_{DSS}	-45			V	$I_D=-100\mu A, V_{GS}=0V$
Gate-Source Threshold Voltage	$V_{GS(th)}$	-1		-3.5	V	$I_D=-1mA, V_{DS}=V_{GS}$
Gate Body Leakage	I_{GSS}			-20	nA	$V_{GS}=-15V, V_{DS}=0V$
Zero Gate Voltage Drain Current	I_{DSS}			-500	nA	$V_{GS}=0V, V_{DS}=-25V$
Static Drain-Source on-State Resistance (1)	$R_{DS(on)}$			14	Ω	$V_{GS}=-10V, I_D=-200mA$
Forward Transconductance (1)(2)	g_{fs}		150		mS	$V_{DS}=-10V, I_D=-200mA$
Input Capacitance (2)	C_{iss}		60		pF	$V_{GS}=0V, V_{DS}=-10V$ $f=1MHz$
Turn-On Time (2)(3)	$t_{(on)}$			20	ns	$V_{DD} \approx -25V, I_D=500mA$
Turn-Off Time (2)(3)	$t_{(off)}$			20	ns	

(1) Measured under pulsed conditions. Pulse width=300μs. Duty cycle ≤ 2% (2) Sample test
(3) Switching times measured with a 50Ω source impedance and <5ns rise time on a pulse generator