

Zebra Technologies

ZQ520

Serial Number:



XXRB1152000559

PCC: ZQ52-AUE000E-00

Name: XXRB1152000559

Program:

OS:6.5.0

PLD: 8 Rev. 32

PSPT: 5 Rev. 23

PMCU: Rev. 11

Firmware:V76.20.10Z

Checksum:7313

Universal Serial Bus:

2.0 Full Speed Device

Vendor ID No: 0x0A5F

Product ID No: 0x010E

Manufacturer String: Zebra Technologies

Product String: ZTC ZQ520-203d

pi ZPL

ID string: off

Bluetooth:

iOS: supported

Version: 5.5.2

Date: 10/03/2017

Baud: 115200

Device: Printer

Mode: Slave

Friendly Name: XXRB1152000559

Minimum Security Mode: 1

Discoverable: on

Bluetooth Spec: 4.0

Enabled: on

Address: 00:17:E9:D8:2E:FD



0017E9D82EFD

Product support website:

<http://zebra.com/zq520-info>



Peripherals:

MCR: Not installed

NFC: Not installed

LCD: Installed

Power Management:

In-activity Timeout:36000 Secs

Low-battery Timeout:60 Secs

Remote(DTR) pwr-off:Enabled

Voltage :7.83

Low-bat Warning :6.93(176)

Low-bat Shut-down:6.53(166)

Power On Cycles :2037

Battery Health :replace

Battery Cycle Count: 212

Memory:

Flash :67108864 Bytes
RAM :8388608 Bytes

Label:

Width :832 dots, 104 mm
Height:65535 dots, 8191 mm

Sensors: (Adj)

Front Bar [DAC:98,Thr:70,Cur:1

2]

Back Bar [DAC:103,Thr:70,Cur:0

]

Gap [DAC:147,Thr:50,Cur:62]

Temperature :28C (56)

Voltage :7.8V (199)

Resident Fonts:

Font	Sizes	Chars
0	0- 6	20-FF
1	0	20-80
2	0- 1	20-59
4	0- 7	20-FF
5	0- 3	20-FF
6	0	20-44
7	0- 1	20-FF

File Directory:

File	Size
E:CONFIG.SYS	31
E:TT0003M_.TIF	169188
66938880 Bytes Free	

Command Language:

CCL Key '!' [21]

ZPL Configuration Information:

```

Rewind.....Print Mode
Continuous.....Media Type
30.0.....Darkness
+00.....Tear Off Adjust
2030.....Label Length
104mm.....Print Width
7Eh.....Control Prefix
5Eh.....Format Prefix
2Ch.....Delimiter
00.....Top Position
No Motion....Media Power Up
Feed.....Media Head Closed
00.....Left Margin
832.....Dots per row
End ZPL Configuration

```

Printhead test: OK
End of report.

**Press FEED key to
enter DUMP mode.**

Dump mode not entered.