



Xitanium LED downlight and spotlight drivers

Xitanium 30W/m 0.35-0.7A 44V DS I 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	700 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	30 W
Output Power (Min)	9 W
Output Current (Min)	350 mA
Output Voltage (Max)	44 V
Output Voltage (Min)	5 V
System characteristics	
Central DC Operation	Yes
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	80 °C
T-Case Maximum (Max)	80 °C

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Product Length	156 mm
Overall length	156 mm
Overall width	43 mm
Overall height	30 mm
Dimensions (Height x Width x Depth)	30 x 43 x 156 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	Dipswitch
Protection class IEC	Safety class I/II
Product Data	
Order product name	Xitanium 30W/m 0.35-0.7A 44V DS I 230V
Full product name	Xitanium 30W/m 0.35-0.7A 44V DS I 230V

Xtanium LED downlight and spotlight drivers

Full product code	871951439630200
Order code	929002880106
Material Nr. (12NC)	929002880106
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.122 kg

EAN/UPC - Product/Case	8719514396302
Numerator - Packs per outer box	40
EAN/UPC - Case	8719514396319

