

## **Technical Data Sheet**

### **Bird Brand Danish Oil**



Description	A satin finish obtained from a blend of oils and an air drying resin.
Usage/purpose	Wood turning, furniture, doors, wooden paneling, interior joinery, skirting etc.
Characteristics	A penetrating finish that brings out the natural beauty of wood.
Performance	Resists scratching, will not chip.
Finish	Satin Sheen
Colour	Amber
Composition	Based on a high quality oils and resins.
Properties	VOC Content High 25-50%
Finish	Satin sheen
Colour(s)	Clear
Packaging	250ml, 500ml, 1 Litre, 2.5 Litre, 5 Litre, 25 Litre.
Composition	Based on high quality oils and resins
Properties	VOC Content: High 25 – 50%
Performance	Interior or exterior finish. NB. If used externally, will require regular maintenance (at least annually) Ensure the substrate to be oiled is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish, etc) Ensure the Danish Oil is thoroughly shaken.

## Bird Brand Danish Oil

Apply liberally with a brush or lint free rag. Allow to soak into wood for 10 – 20 mins then wipe off the excess.

Recommended Spreading Rate	14m <sup>2</sup> /l
Drying Time	Touch dry in 2-4 hours. Re-coatable after 16 hours under normal drying conditions (20°C 50% r/h)
Cleaning	Clean application equipment or spills with white spirit or brush cleaner.
Limitations	When used outside finish must be maintained regularly (at least once a year)
Environmental Info	Dangerous to the environment

**Full Material Safety Data Sheets are available from [www.birdbrand.co.uk/msds.htm](http://www.birdbrand.co.uk/msds.htm) or alternatively please contact us at the details given below.**

**Bird Brand ® is a registered trademark of R K & J Jones Limited, Southery Road, Feltwell, Thetford, Norfolk, IP26 4EH. UK.  
Tel. 01842 828101 Fax. 01842 828171  
[www.birdbrand.co.uk](http://www.birdbrand.co.uk)  
Email: [admin@birdbrand.co.uk](mailto:admin@birdbrand.co.uk)**