


POSDC-T-PPL21-0.4 series

DC Power Cable



model

POSDC-T-PPL21-0.4 power cable **400mm** long, two angle plug 2.1x5.5x10mm

mechanical specification

<i>connector type (output)</i>	angle plug 2.1x5.5x10 mm (inner diameter / outer diameter / length)
<i>connector type (input)</i>	angle plug 2.1x5.5x10 mm (inner diameter / outer diameter / length)
<i>length</i>	400mm
<i>wire diameter</i>	2x0.35mm ²
<i>wire construction</i>	pure copper core, flexible, multiwire conductors
<i>jacket</i>	PVC - double insulation
<i>inner conductor</i>	Cu
<i>cable cross section</i>	3.6 mm
<i>color of the cores</i>	black

electrical specification

<i>nominal voltage</i>	0 - 60V
<i>rated current</i>	2A
<i>Insulation resistance</i>	>100M Ω @ 300Vdc
<i>Insulation thickness</i>	0.4mm
<i>Wire resistance</i>	max 0.039 Ω /m
<i>Working Temperature</i>	-20°C ÷ 80°C

safety


<i>RoHS</i>	RoHS 2015/863
<i>LVD</i>	LVD 2014/35/UE

POSDC-T-PPL21-0.4 series

DC Power Cable



mechanical specification



connection

