



/ Portable EVELINE MAX II

- › 11 kW AC portable charger
- › Extremely durable, maintenance - free and waterproof
- › One of the smallest chargers on the market
- › Safety features including integrated RCCB-A-EV (30mA AC / 6mA DC) residual current breaker
- › Consumption measurement
- › Adjustable charging current 6 - 16A



/ Sales advantages

THE SMALLEST DIMENSIONS ON THE MARKET

We have developed the smallest portable charger with OLED LCD display and other functions while maintaining all high-standard protection elements (including detection of DC leakage currents)

HIGH RESISTANCE

EVELINE MAX II is made of a special aluminum alloy profile for the highest durability. At the same time, it is also 100% waterproof. It works at temperatures ranging from -40 ° C to 50 ° C.

CHARGING POWER UP TO 11kW

EVELINE MAX II automatically adapts to the current connection point. If 16A is available, a 11kWh battery can be charged in 1 hour.

ADJUSTABLE CHARGING CURRENT

Thanks to the built-in button, the charging current can be easily set according to the circuit breaker options. The setting range is 6 - 8 - 10 - 13 - 16A.

Advantages of OLED LCD

Easy and intuitive setting of charging parameters, charging status, operating temperature, consumed kW / h and voltage on each phase:



/ Specifications

Maximum charging power	11kW (3 phase)
Charging power settings	3,7kW / 4,6kW / 6,9kW / 7,4kW / 11kW
Rated current	16A
Voltage	250V (1 phase) / 400V (3 phase)
Dimensions	50 x 80 x 190mm (V x Š x H)
Weight	3.kg (5m), 5.1kg (8m)
The cable length	5 - 8m
Safety elements	Permanent protection of residual resistance. RCCB-A-EV (30mA AC / 6mA DC).
Degree of protection	IP65
Connector type	Car side - TYPE 2 (compliant with IEC 62196). Grid side - industrial socket CEE 32A 5-pin.
Permissible ambient temperature	-30°C to + 50°C (-22F to 122F)
Display	1,3" OLED
Communication	Compliant with IEC 61851-1, Mode 2
Color	Gold (body), Black (charging cable)
Adapter options	CEE plug 16A, schuko
A part of the package	Portable charging station, manual, bag
Warranty	3 years