

Specyfikacje



Zdjęcie jest reprezentatywne

Eaton 266685

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 208-240VAC, for size 4

General specifications

PRODUCT NAME	Eaton Moeller series NZM remote operator
CATALOG NUMBER	266685
EAN	4015082666859
PRODUCT LENGTH/DEPTH	189 mm
PRODUCT HEIGHT	202 mm
PRODUCT WIDTH	210 mm
PRODUCT WEIGHT	6.1 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	CSA certified CSA (Class No. 1437-01) UL listed UL489 UL (File No. E140305) UL (Category Control Number DIHS) CE marking IEC60947 CSA (File No. 22086) CSA-C22.2 No. 5-09
MODEL CODE	NZM4-XR208-240AC



Powering Business Worldwide

Elektryczne dane techniczne

VOLTAGE TYPE	AC
VOLTAGE RATING	208 - 240 V 50/60 Hz
OPERATING VOLTAGE - MIN	0.85 x Us
OPERATING VOLTAGE - MAX	1.1 x Us
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
VOLTAGE TOLERANCE - MIN	0.85
VOLTAGE TOLERANCE - MAX	1.1
RATED OPERATING FREQUENCY	50 Hz
POWER CONSUMPTION	350 VA (110 - 130 V AC)
CLOSING DELAY	100 ms
BREAKING TIME	3000 ms
NUMBER OF OPERATIONS PER HOUR - MAX	20
SIGNAL DURATION OF REMOTE OPERATOR AT SWITCH OFF - MIN	500 ms
SIGNAL DURATION OF REMOTE OPERATOR AT SWITCH ON - MIN	30 ms

Mechaniczne dane techniczne

SWITCH DRIVE TYPE	Motor drive
LIFESPAN, MECHANICAL	10000 operations

Komunikacyjne dane techniczne

OPERATING VOLTAGE - MIN	0.85 x Us
OPERATING VOLTAGE - MAX	1.1 x Us
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	0 V
VOLTAGE TOLERANCE - MIN	0.85
VOLTAGE TOLERANCE - MAX	1.1
RATED OPERATING FREQUENCY	50 Hz
POWER CONSUMPTION	350 VA (110 - 130 V AC)
CLOSING DELAY	100 ms
BREAKING TIME	3000 ms
NUMBER OF OPERATIONS PER HOUR - MAX	20
SIGNAL DURATION OF REMOTE OPERATOR AT SWITCH OFF - MIN	500 ms
SIGNAL DURATION OF REMOTE OPERATOR AT SWITCH ON - MIN	30 ms

Do pobrania

DEKLARACJE ZGODNOŚCI

[eaton-accessories-declaration-of-conformity-eu250141en.pdf](#)

INSTRUKCJE MONTAŻU	eaton-nzm4-romete-operator-xr-il01210006z.pdf
MODELE ECAD	ETN.266685.edz
MODELE MCAD	DA-CD-nzm4_xr DA-CS-nzm4_xr
RYSUNKI	eaton-circuit-breaker-remote-operator-nzm-remote-operator-dimensions-003.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

Follow us on social media to get the latest product and support information.

