

	Document:	Division:		Date of modification:
	Technical data sheet	Quality Control		04.07.2017
Product:	Label Paper – COPP (Acrylic)			

Self-adhesive label, paper, white.

1. Technical specification - Face

Feature	Unit	Value
Weight	[g/m ²]	75 [+/-3%]
Thickness	[my]	98 [+/-3%]
Opacity	[%]	>93 [-2]
Whiteness		167 [+/-3]
Relative humidity	[%]	35 [+/-5]
Tensile strength:		
Machine direction	[N]	>70 [-5]
Transverse direction	[N]	>32 [-3]

2. Technical specification - Glue

Feature	Unit	Value
Weight of glue	[g/m ²]	17
Adhesion at 180°	[N/inch]	≥10
Shear	[hours]	120

3. Technical specification - Liner

Feature	Unit	Value
Type of liner		45wCCco
Thickness	[my]	51
Weight	[g/m ²]	45
Tensile strength:		
Machine direction	[kN/m]	3,9
Transverse direction	[kN/m]	1,7
Brightness	[%]	78

4. Printability:

- a. Digital, laser, inkjet printers.
- b. Photocopying.

5. Recommendations:

- a. The product must be stored in dry areas (relative humidity 50%).
- b. The product must be protected from direct sunlight.
- c. Before usage, the product must be stored in its original packaging, avoiding incorrect handling, accidental bumps and especially edge cuts. Product can not be stacked.
- d. The product must be stored at a constant temperature of 20 ° C (+/- 2 °C).
- e. Application temperature: from +5 °C.
- f. Operating temperature: from -5 °C to +50 °C.

6. Shelf life:

Shelf life is up to two years when complying with the above recommendations for storage.

Warranty and tolerances available on www.euro-tape.pl in customer zone.