



Yuasa Technisches Datenblatt

Yuasa YBX9020 - YBX9000 AGM Start Stop Plus Batterien

Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	105Ah
Kaltstartstrom (A) EN1	950A

Abmessungen

Länge	393mm
Breite	175mm
Höhe	190mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	29.6kg
--	--------



Gehäuseeigenschaften

Gehäusotyp	L6 DIN AGM
Batteriehalter	B3
Tragegriffe	✓
Entgasung	✓
Semi Traktionseigenschaften	✓
Deckeltyp	VRLA


Technologie

Flammschutz	✓
Technologie	Ca/Ca VRLA
Adskiller	AGMSORTIMENT
VDA Überschlagentest	✓
Empfohlener Ladestrom	6A
Performance Marking	W5-C2-V3-M3


Anschlusspol Typ

T1


Standard DIN Post



Zellenanordnung



Batteriehalter



Datenblatt erstellt am 30/08/2023 - E&EO



Yuasa Technical Data Sheet

Yuasa YBX9020 - YBX9000 AGM Start Stop Plus Batteries

Performance

Voltage	12V
Capacity (20-hour)	105Ah
Cold Cranking Amps (EN1)	950A

Dimensions

Length	393mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	29.6kg
-----------------------	--------



Container Features

Case Type	L6 DIN AGM
Hold Down	B3
Handles	✓
End Venting	✓
Semi-Traction Features	✓
Lid Type	VRLA


Technology

Flame Arrestor	✓
Technology	Ca/Ca VRLA
Separator	AGM
VDA Roll Over Test	✓
Recommended Charge Rate	6A
Performance Marking	W5-C2-V3-M3


Terminal Type

T1


Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 30/08/2023 - E&OE