


6-4

비상 누름 버튼 스위치 (A-Type) Emergency Push Button Switch (A-Type)

■ **Yong Sung** File No. E242380

형식 구분도 | Type Classification Diagram |



성능 개요 | Performance Summary |

절연저항 (Insulation resistance)	above 100MΩ (DC 500V. Meg)
접촉저항 (Contact resistance)	below 50mΩ (Initial value)
내전압 (Withstand voltage)	AC 2,500V/min (60Hz)
기계적수명 (Mechanical lifetime)	above 500,000 times (20times/min)
전기적수명 (Electrical lifetime)	above 100,000 times (20times/min)
사용주위온도 (Ambient temperature)	-25℃ ~ 40℃
상대습도 (Relative humidity)	45% ~ 85%



접점 정격 | Contact Rating |

정격절연전압 (Rating insulation voltage)		AC600V, DC250V		
정격통전전류 (Rating conductive current)		10A		
AC	정격전압 (Rated votage)	110V	220V	440V
	저항부하 (Resistive load)	10A	6A	3A
	유도부하 (Inductive load)	5A	2.5A	1.2A
DC	정격전압 (Rated votage)	110V	125V	220V
	저항부하 (Resistive load)	2.2A	1.9A	1.1A
	유도부하 (Inductive load)	1.1A	1.0A	0.6A



외형 / 치수도 | Shape / Dimension Drawing

(unit : mm)

Ø25



Ø30



판넬 가공 치수 | Cut-out Dimension

(unit : mm)

