

DIN15W5

5V/10W Din Rail Power Supply



■ Features:

- Constant voltage design
- European AC input range
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
 - Isolation class II
- Can be installed on DIN Rail TS-35/7 or 15
 - MTBF 200.000 h

SELV   

ELECTRICAL SPECIFICATION

MODEL		DIN15W5					
OUTPUT							
Rated Voltage		5V					
Rated Current		2A					
Current Range		0 ÷ 2A					
Rated Power		10W					
No Output Voltage (max)		5.4V					
Voltage Adjustment Range [6]		4.25 – 5.75V					
Line Regulation		± 1%					
Load Regulation		± 1%					
Tolerance [3]		± 5%					
Ripple & Noise (max.) [2]		100mV _{P-P}					
Setup, Rise Time [4]		max 820ms, 70ms / 230VAC at full load					
Hold up Time (typ.)		65ms / 230VAC at full load					
INPUT							
Voltage Range		180 ÷ 264VAC					
Frequency Range		47 ÷ 63Hz					
Inrush current		75A at 230VAC cold start at 25°C					
Efficiency (typ.)		>78.04% - Average (25%+50%+75%+100%) /4					
AC Current (typ.)		0.35A / 230VAC					
Leakage current		<1.5mA at 50/60Hz 240VAC INPUT					
Max. No. Of PSU on Circuit Breaker		B10	B16	C10	C16	D10	D16
		22	35	22	35	45	72
No load Power Consumption (max.)		<0.5W					

DIN15W5

5V/10W Din Rail Power Supply



PROTECTIONS

Over Current	Range 120 ÷ 180%
	Type: hiccup mode. Recovers automatically after fault condition is removed.
Short Circuit	Type: hiccup mode. Recovers automatically after fault condition is removed.
Over Voltage	9V-10V
	Type: hiccup mode. Recovers automatically after fault condition is removed.
Over Temperature	Range: NTC detect
	Type: shut down output voltage. Re-power on to recovery.

WORKING ENVIRONMENT

Working Temperature	-20°C ÷ +50°C, ambient derate each output at 4.0% per degree from 50°C to 60°C
Working Humidity	5 ÷ 95% RH non-condensing
Storage Temperature and Humidity	-30°C ÷ +70°C, 5 ÷ 95% RH non-condensing

SAFETY and EMC REGULATIONS

Safety Standards	Compliance to EN 62368-1
Withstand Voltage	IN/OUT: 3kVAC, IN/GND: 2kVAC, OUT/GND: 0.5kVAC
EMC Emission	Compliance to EN55032
EMC Immunity	Compliance to EN55035
Harmonic Current	Compliance to EN61000-3-3; EN61000-3-2

OTHERS

Dimensions	25 x 92.5 x 56mm (L x W x H)
Weight and Packing	94g; 100pcs. /box; weight box and dimensions: 10.5kg; 33.3 x 23.3 x 33.5cm

MECHANICAL SPECIFICATION

PIN ASSIGNMENT

NO.	Assignment
1	Input: AC/N
2	Input: AC/L
3	Output: U _{OUT} +
4	Output: U _{OUT} -
7	LED indication for power on
8	U _{OUT} adjustment




DIN15W5

5V/10W Din Rail Power Supply



MECHANICAL SPECIFICATION:



1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF i 47μF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.
6. By built-in potentiometer.