


# LED DOWNLIGHT

Product&Family Code:

016 087 0030

**ALEXIS-30 3CCT**



**BLACK**

**WHITE**

## Technical Data

|                                                 |                                                                                     |
|-------------------------------------------------|-------------------------------------------------------------------------------------|
| Voltage (V)                                     | 160-265V                                                                            |
| Product Wattage (W)                             | 30W/3CCT                                                                            |
| Equivalence with incandescent lamp              | 240                                                                                 |
| Colour Render Index (Ra)                        | >Ra70                                                                               |
| Colour Temperature (K)                          | 3000K-4500K-6000K                                                                   |
| Materials                                       | Plastic                                                                             |
| Protection Class                                | II                                                                                  |
| Dimmable                                        | No                                                                                  |
| EEI                                             |  |
| Warm-up time up to 60 %of the full light output | Instant Full Light                                                                  |
| Luminous Flux (lm)                              | 3000                                                                                |
| Luminous Efficacy (lm/W)                        | 100                                                                                 |
| Rated Life (hrs) ⌚                              | 30.000                                                                              |
| IP Rating                                       | 20                                                                                  |
| Power Factor                                    | >0.5                                                                                |
| Beam Angle                                      | 120°                                                                                |
| Starting Time                                   | <0.2s                                                                               |
| Number of ON-OFF cycling                        | x15.000                                                                             |

## CCT ADJUSTABLE

CCT Selectable by DIP Switch




## Applications

- Airport, Bathroom, Bedroom, Car Park, Cinema, Gallery, Hospital, Hotel, Kitchen, Museum etc.



## Technical Drawing



## Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- SMD LED Lamp Base.

