

[Back](#)

ThinkPad Universal Thunderbolt 4 Dock – EU/Indonezja /Wietnam/Korea Południowa

40B00135EU



2291 views

List Price (Tax excluded) [PRODUCT BROCHURE](#)

-

[Compare](#)

FEATURE

TECH SPECS

Feature

Product Description

Stacja dokująca Universal Thunderbolt™ 4 klasy korporacyjnej: stacja dokująca ThinkPad Universal Thunderbolt 4 Dock zapewnia niezawodną i spójną czołową w branży łączność danych, wideo i zasilania w środowisku mieszanych komputerów PC opartych na systemie Windows. ; Zmaksymalizuj produktywność: poszerz swoje horyzonty dzięki wszechstronnej obsłudze wyświetlaczy 8K lub wielu wyświetlaczy 4K, cichej aktualizacji oprogramowania sprzętowego, obsłudze VPro/AMT i przesyłaniu danych z prędkością 40 Gbps. ; ThinkPad Universal Thunderbolt 4 jest przyszłościowa i w pełni wyposażona, aby przenieść Twoją produktywność, wydajność i kreatywność na szczyt.

Top Features

- Stacja dokująca ThinkPad Universal Thunderbolt™ 4 Dock obsługuje do 100 W PD, pojedynczy wyświetlacz 8K przy 30 Hz lub do 4 wyświetlaczy 4K przy 60 Hz, cichą aktualizację oprogramowania sprzętowego oraz zapewnia obsługę przekazywania vPro/AMT, a także szybkość transferu danych do 40 Gbps (w zależności od możliwości przetwarzania systemu hosta i urządzeń peryferyjnych, atrybutów plików oraz innych czynników konfiguracji i środowiska operacyjnego).

More Information

[Technical Support](#)[Dock Driver](#)[Display Resolution](#)

Tech Specs

Supported OS	Win10 (wersja 64), Win 11 (wersja 64)
Minimum Relative Humidity (%)	5%

[TOP](#)

Maximum Relative Humidity (%)	95%
JAN	4580551376145
EAN	195348677325
UPC	195348677325
Warranty Type	CRU
Warranty Period	3 lata
Maximum Operating Temperature	40 stopniu Celsiusza
Minimum Operating Temperature	0 stopniu Celsiusza
Packed Weight	1,2 kg
Packed Dimensions (L x D x H)	270 x 195 x 85 mm
Package Type	brązowe pudełko
Shipment Group	ThinkPad Universal TBT 4 Dock Zasilacz 135 W Kabel zasilający Plakat konfiguracyjny i gwarancyjny Standardowy kabel TBT 4
Included Accessory	Zasilacz 135 W, 1 kabel zasilający, standardowy kabel Thunderbolt
Product Weight	0,45 kg
Height	30 mm
Depth	80 mm
Length	220 mm
Driver Needed	Tak
Hardware Requirements	Host z portem USB-C/Thunderbolt

[TOP](#)

Agency Approvals	CE-EMC, TUV Mark, KCC, serbski Kvalitet, CU EAC
Color	Czarny/czerwony
Power Plug	Wąska końcówka
Power Button	Tak
Output Power	Maksymalnie 100 W
Power Delivery	Tak
Input Power	20 V 6,75 A
Charging Port	DC-IN
Maximum Resolution/Refresh Rate	1* 8K 30 Hz przez HDMI 2.1 4*4K 60 Hz
Max Number of External Monitors	4
Physical Security Feature	1* gniazdo blokady NanoSaver 1* gniazdo blokady MicroSaver
Ethernet	1* Gigabit Ethernet
Audio Ports	1* gniazdo combo audio 3,5 mm typu „jack”
USB Ports	4* USB-A 1 złącze USB-C
Video Ports	1* HDMI 2.1 2* DP 1.4
Thunderbolt Port	1* port Thunderbolt — do podłączania hosta 1* port Thunderbolt — do podłączania urządzenia
Brand	ThinkPad

Compatibility

Operating System

OS Independent

Compatible Machines

Description	ID	Footnote
-------------	----	----------

[TOP](#)

L13 Clam 2nd Generation-20VH MT 2020	20VH	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
L13 Clam 2nd Generation-20VJ MT 2020	20VJ	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
L13 Clam G3-21B3 - L13 Clam Gen 3	21B3	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
L13 Clam G3-21B4 - L13 Clam Gen 3	21B4	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
L13 Clam-20R3 MT	20R3	PXE boot supported. Wake On LAN from Sleep, Hibernation, or Power-Off mode.MAC address pass through.
L13 Clam-20R4 MT	20R4	PXE boot supported. Wake On LAN from Sleep, Hibernation, or Power-Off mode.MAC address pass through.
L13 Yoga 2nd Generation-20VK MT 2020	20VK	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
L13 Yoga 2nd Generation-20VL MT 2020	20VL	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
L13 Yoga G3-21B5 - L13 Yoga Gen 3	21B5	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
L13 Yoga G3-21B6 - L13 Yoga Gen 3	21B6	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
L13 Yoga-20R5 MT	20R5	PXE boot supported. Wake On LAN from Sleep, Hibernation, or Power-Off mode.MAC address pass through.
L13 Yoga-20R6 MT	20R6	PXE boot supported. Wake On LAN from Sleep, Hibernation, or Power-Off mode.MAC address pass through.
L14 G2-20X1 - L14 Gen 2	20X1	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
L14 G2-20X2 - L14 Gen 2	20X2	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
L14 G3-21C1 - L14 Gen 3	21C1	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through


[TOP](#)

L14 G3-21C2 - L14 Gen 3	21C2	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
L15 G2-20X3 - L15 Gen 2	20X3	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
L15 G2-20X4 - L15 Gen 2	20X4	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
L15 G3-21C3 - L15 Gen 3	21C3	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
L15 G3-21C4 - L15 Gen 3	21C4	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P14s 2nd Generation-20VX MT 2021	20VX	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P14s 2nd Generation-20VY MT 2021	20VY	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P14s G3-21AK MT 2022	21AK	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P14s G3-21AL MT 2022	21AL	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P15s 2nd Generation-20W6 - P15s Gen 2	20W6	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P15s 2nd Generation-20W7 - P15s Gen 2	20W7	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P15v G3-21D8 - P15v Gen 3	21D8	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P15v G3-21D9 - P15v Gen 3	21D9	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P16s AMD G1-21CK - P16s AMD Gen 1	21CK	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P16s AMD G1-21CL - P16s AMD Gen 1	21CL	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through


[TOP](#)

P16s G1-21BT - P16s Gen 1	21BT	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
P16s G1-21BU - P16s Gen 1	21BU	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14 2nd Generation-20W0 MT 2021	20W0	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14 2nd Generation-20W1 MT 2021	20W1	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14 2nd Generation-20W2 MT 2021 HC	20W2	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14 2nd Generation-20W3 MT 2021 HC	20W3	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14 AMD G3-21CF - T14 AMD Gen 3	21CF	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14 AMD G3-21CG - T14 AMD Gen 3	21CG	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14 G3-21AH - T14 Gen 3	21AH	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14 G3-21AJ - T14 Gen 3	21AJ	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14s 2nd Generation-20WM - T14s Gen 2	20WM	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14s 2nd Generation-20WN - T14s Gen 2	20WN	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14s G3-21BR - T14s Gen 3	21BR	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T14s G3-21BS - T14s Gen 3	21BS	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through



T15 2nd Generation-20W4 - T15 Gen 2	20W4	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T15 2nd Generation-20W5 - T15 Gen 2	20W5	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T15p G3-21DA - T15p Gen 3	21DA	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T15p G3-21DB - T15p Gen 3	21DB	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T16 AMD G1-21CH - T16 AMD Gen 1	21CH	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T16 AMD G1-21CJ - T16 AMD Gen 1	21CJ	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T16 G1-21BV - T16 Gen 1	21BV	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
T16 G1-21BW - T16 Gen 1	21BW	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
ThinkBook 13s G4 IAP-21AR - ThinkBook 13s G4 IAP	21AR	
ThinkPad L14-20U1 MT 2020	20U1	PXE boot supported. Wake On LAN from Sleep, Hibernation, or Power-Off mode.MAC address pass through.
ThinkPad L14-20U2 MT 2020	20U2	PXE boot supported. Wake On LAN from Sleep, Hibernation, or Power-Off mode.MAC address pass through.
ThinkPad L15-20U3 MT 2020	20U3	PXE boot supported. Wake On LAN from Sleep, Hibernation, or Power-Off mode.MAC address pass through.
ThinkPad L15-20U4 MT 2020	20U4	PXE boot supported. Wake On LAN from Sleep, Hibernation, or Power-Off mode.MAC address pass through.
ThinkPad T14-20S0 MT 2020	20S0	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
ThinkPad T14-20S1 MT 2020	20S1	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
ThinkPad T14-20S2 MT 2020 HC	20S2	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through



ThinkPad T14-20S3 MT 2020 HC	20S3	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
ThinkPad T14s-20T0 MT 2020	20T0	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
ThinkPad T14s-20T1 MT 2020	20T1	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
ThinkPad T15-20S6 MT 2020	20S6	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
ThinkPad T15-20S7 MT 2020	20S7	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
ThinkPad X13 series- X13 Yoga G3	21AW	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Carbon 8th Generation-20U9 MT 2020	20U9	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Carbon 8th Generation-20UA MT 2020	20UA	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Carbon 9th Generation-20XW - X1 Carbon Gen 9	20XW	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Carbon 9th Generation-20XX - X1 Carbon Gen 9	20XX	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Carbon G10-21CB - X1 Carbon Gen 10	21CB	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Carbon G10-21CC - X1 Carbon Gen 10	21CC	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Nano G2-21E8 - X1 Nano Gen 2	21E8	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Nano G2-21E9 - X1 Nano Gen 2	21E9	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Nano-20UN MT 2020	20UN	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Nano-20UQ MT 2020	20UQ	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through


[TOP](#)

X1 Titanium G1-20QA MT 2020	20QA	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Titanium G1-20QB MT 2020	20QB	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Yoga 5th Generation-20UB MT 2020	20UB	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Yoga 5th Generation-20UC MT 2020	20UC	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Yoga 6th Generation-20XY - X1 Yoga Gen 6	20XY	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Yoga 6th Generation-20Y0 - X1 Yoga Gen 6	20Y0	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Yoga G7-21CD - X1 Yoga Gen 7	21CD	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X1 Yoga G7-21CE - X1 Yoga Gen 7	21CE	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X12 Detachable 1st Generation-20UV MT 2020	20UV	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
X12 Detachable 1st Generation-20UW MT 2020	20UW	Please connect the dock to the Thunderbolt 4 port on the system side to have full function display support. P1W45M1. PXE boot supported. Wake On LAN from Hibernation, Power-Off mode. MAC address pass through
X13 G1-20T2 MT 2020	20T2	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X13 G1-20T3 MT 2020	20T3	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X13 G2-20WK - X13 Gen 2	20WK	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X13 G2-20WL - X13 Gen 2	20WL	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X13 G3-21BN - X13 Gen 3	21BN	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through


[TOP](#)

X13 G3-21BQ - X13 Gen 3	21BQ	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X13 Yoga 2nd Generation-20W8 MT 2021	20W8	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X13 Yoga 2nd Generation-20W9 MT 2021	20W9	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through
X13 Yoga G3-21AX - X13 Yoga Gen 3	21AX	P1W45M1. PXE boot supported. Wake On LAN from Hibernation,Power-Off mode.MAC address pass through

