

off switch 40A 3-pole



Model	
Product brand name	SENTRON
Product designation	On/Off switches
Design of the switching function	Switch disconnecter
General technical data	
Number of poles	3
Short-circuit current rating	10 kA
Supply voltage	
Type of voltage	AC
Operating voltage / rated value	440 V
Protection class	
Protection class IP	Other
Switching capacity	
Switching capacity current / rated value	0.12 kA
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	0.9 W

Main circuit	
Operating current / rated value	40 A
Product details	
Product component / Signal lamp	No
Number of NO contacts	3
Product function	
Product function / positive opening (acc. to DIN VDE 0113)	No
Connectable conductor cross-section / for flexible conductor / with core end processing	
• minimum	1 mm ²
• maximum	35 mm ²
Connectable conductor cross-section / for rigid conductor	
• minimum	1 mm ²
• maximum	35 mm ²
Mechanical Design	
Height	89.8 mm
Depth	74.5 mm
Installation depth	70 mm
Number of width units	3
Net weight	308 g
Certificates	
General Product Approval	Declaration of Conformity
 CCC	 VDE
 EG-Konf.	Miscellaneous
Further information	
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TL1340-0	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/5TL1340-0	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL1340-0	
CAX-Online-Generator http://www.siemens.com/cax	
Tender specifications http://www.siemens.com/specifications	

