



Note: This datasheet may be out of date. Please download the latest datasheet of CSTCE8M00G15C99-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCE8M00G15C99-R0

# CSTCE8M00G15C99-R0










## Appearance & Shape







### **Features**

MURATA's frequency adjustment and packaging technology expertise has enabled the development of the chip CERALOCK(R) with built-in load capacitors.

This diverse series owes its development to MURATA's original mass production techniques and high reliability, and has achieved importance in the worldwide automotive market.

### Features

- 1. High accuracy resonators whose total tolerance is available for less than +-3,000ppm.
- 2. High reliability and available for a wide temperature range.
- 3. Oscillation circuits do not require external load capacitors.
- 4. Available for a wide frequency range.
- 5. Extremely small and have a low profile.
- 6. No adjustment is necessary for oscillation circuits.



## **Applications**

Automotive Usage	Powertrain/Safety
Other Usage	Automotive



## Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Embossed Tape	3000

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





### Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSTCE8M00G15C99-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCE8M00G15C99-R0

# CSTCE8M00G15C99-R0



# **Specifications**

	Ceramic Resonator	
Product Type		
	(CERALOCK)	
Series	CSTCE_G_C	
Frequency	8.000MHz	
Frequency Tolerance	+/-0.10% max.	
Operating Temperature	1000 1000	
Range	-40°C~125°C	
Frequency Shift by	( 0 400)	
Temperature	+/-0.13% max.	
Frequency Aging	+/-0.07% max.	
. , , ,		
Resonant Impedance (R1)	40ohm max.	
Built-in Load Capacitance	22-5	
(CL1/CL2)	33pF	
Shape	SMD	
Wash	available	
VVGGII	availabic	
L x W (size)	3.2x1.3mm	
Mass	11mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

