



Black Jade-Flow

DOUBLE-TRANSPARENT GLASS BIFACIAL N-TYPE MODULE

490~500 W



Cutting Free Technology
Minimized micro-crack



Bifacial Mono Module
Capable of generating power at back side, at least 80% efficiency of the front side



Anti-PID (potential induced degradation)
Passed anti-PID test under 85% damp heat 85% relative humidity for 192 hours



Higher Power Output
Lower shading and resistive loss



Outstanding mechanical load resistance
2400 Pa wind load, 5400 Pa snow load



15 15-year product warranty

30 30-year linear power output



CEC Listed



IEC 61215, IEC 61730

ISO 9001: 2015 (Quality management systems)

ISO 14001: 2015 (Environmental management systems)

ISO 45001: 2018 (Occupational health and safety)

UNI 9177 Ia CLASSE DI REAZIONE AL FUOCO: 1

Add: No. 238 Yunlin Middle Road, Wangchun Industrial District, Ningbo, China

Tel: +86-574-28828939

Email: sales@ulsolar.com.cn

Fax: +86-574-28828997

Web: www.ulicasolar.com



TOPCon(N TYPE) 490~500Watt



ELECTRICAL SPECIFICATIONS


Module Type		UL-490M-120BDGN		UL-495M-120BDGN		UL-500M-120BDGN	
		STC*	NOCT*	STC*	NOCT*	STC*	NOCT*
Maximum Power (Pmax)	W	490	371	495	375	500	379
Maximum Power Voltage (Vmp)V		36.68	33.75	36.85	33.90	37.02	34.06
Maximum Power Current (Imp) A		13.36	11.00	13.43	11.06	13.51	11.13
Open-circuit Voltage (Voc)	V	43.35	39.45	43.52	39.60	43.78	39.84
Short-circuit Current (Isc)	A	14.35	11.58	14.43	11.64	14.48	11.68
Module Efficiency STC	%	22.14		22.36		22.59	
Operating Temperature				-40°C~85°C			
Maximum system voltage				DC1500V(IEC)			
Maximum series fuse rating				30A			
Power tolerance				0~+5Watt			
Temperature coefficients of Pmax				-0.29%/°C			
Temperature coefficients of Voc				-0.25%/°C			
Temperature coefficients of Isc				0.046%/°C			
Nominal operating cell temperature (NOCT)				43±2°C			

*STC : Cell temperature: 25°C, Irradiance: 1000 W/m², Air mass: 1.5G


*NOCT : Air temperature: 20°C, Irradiance: 800 W/m², Air mass: 1.5G, Wind speed: 1 m/s

I-V CURVE[500W]

I-V characteristics at different irradiances



I-V characteristics at different temperature





SPECIFICATIONS


Cell Type	N type Mono-crystalline	
No. of cells	120(6×10×2)	
Dimensions	1952*1134*30mm	
Weight	26.5kg	
Glass	2.0mm+2.0mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass	
Junction Box	IP68, 3 diodes	
Connector	MC4 Compatible	
Cable Length (Including Connector)	Portrait: (+)400/(-)200mm Landscape: (+)1200/(-)1200mm	
Packaging Configuration	Two Box=One Pallet 36pcs/Box, 72pcs/Pallet, 864pcs/40HQ Container	

Electrical characteristics with different rear side power gain(reference to 500 W front)


Pmax/W	Voc/V	Isc/A	Vmp/V	Imp/A	Pmax gain
500	43.78	14.48	37.02	13.51	0
525	43.78	15.20	37.02	14.18	5%
550	43.78	15.93	37.02	14.86	10%
575	43.78	16.65	37.02	15.53	15%
600	43.78	17.38	37.02	16.21	20%
625	43.78	18.10	37.02	16.88	25%
650	43.78	18.82	37.02	17.56	30%



Section A-A



Section B-B



I

B

Length: ± 2mm
Width: ± 2mm
Height: ± 1mm
Row Pitch: ± 2mm

Specifications included in this datasheet are subject to change without notice.

Ulica Solar reserves the right of final interpretation.

