

FEATURES

Number of buttons: 2


IN-WALL

## Operating plate AC4

PRICE (VAT INCLUDED)

## BGN53.00 BGN.00

TECHNICAL DRAWINGS





## COMPATIBLE WITH



Installation system for floorstanding WC. With compact cistern and dual flush mechanism 6/3, 4.5/3 and 4/2 litres and installation accessories. Minimum depth: 80 mm. (Preset to 4,5/3L)



Installation system for floorstanding WC. With compact cistern and dual flush mechanism 6/3, 4.5/3 and 4/2 litres and installation accessories. Minimum depth: 80 mm. (Preset to 6/3L)



Installation system for wallhung WC. With compact cistern and dual flush mechanism 6/3, 4.5/3 and 4/2 litres and installation accessories. Minimum depth with horizontal outlet: 80 mm Minimum depth with vertical outlet: 90/110 mm



Installation system for wallhung wc, brick wall

890060120



Installation system for wallhung WC. With compact cistern and dual flush mechanism 6/3, 4.5/3 and 4/2 litres and installation accessories. Minimum depth with horizontal outlet: 80 mm Minimum depth with vertical outlet: 107/125 mm



Installation system for wallhung wc, light wall

890060020



## In-Wall

Systems that combine efficiency and technology to deliver the best performance.

