

LED FLAME BULB



Product&Family Code: 001 048 0005

FIREFLUX

Technical Data

Voltage (V)	100-250V
Product Wattage (W)	5
Equivalence with incandescent lamp	40
Colour Render Index (Ra)	>60
Colour Temperature (K)	1500K
Materials	Aluminium Housing with ABS Diffuser
Protection Class	-
Dimmable	No
EEI	-
Warm-up time up to 60 %of the full light output	Instant Full Light
Luminous Flux (lm)	117
Luminous Efficacy (lm/W)	23.4
Rated Life (hrs) ⌚	25,000
IP Rating	-
Power Factor	>0.5
Beam Angle	300°
Starting Time	<0.5
Number of ON-OFF cycling	x12,500

3 Modes



Flame Mode



General Lighting Mode




Breathing Mode



Gravity Sensor

Technical Drawing



E27

Applications

The luminaire is an excellent solutions for garden, restaurant museum etc.



Features

- Low power consumption
- Efficient replacement for incandescent lamps
- Mercury free, no UV and IR radiation
- Instant on, 100% light output

///	12.500X ON / OFF	NO UV / IR	mA 39
%85 ENERGY Saving	25000h Lifetime	0,0mg	Optimally
Start Up Time <0.5	300°	-20°C +45°C	
Ra >60	Warm Up %60 < 0.5 sc.	PF >0.5 Power Factor	

