



Pellet Air Plus

TECHNICAL DATA

Thermic Power (at min-at max)	kW	3,2 - 8,5
Introduced thermal power (at max)	kW	9,4
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	87
Useful efficiency (at min-at max)	%	90 - 90
Heatable volume (at min-at max)	m ³	90 - 238
CO ₂ (min-max)	%	5,4 - 10,7
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	163 - 125
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	1 - 1
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	110 - 100
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	15 - 15
Fuel Pellet	mm	Ø6 L=3÷40
Hopper capacity	kg	20
Hourly consumption (at min-at max)	kg/h	0,7 - 1,9
Autonomy (at min-at max)	h	29 - 11
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	370
Operating electrical absorption (at max)	W	110
Chimney flue depression (at min-at max)	Pa	2 - 11
Mass of smoke (at min-at max)	g/sec	3,6 - 5,3
Exhaust fumes temperature (at min-at max)	°C	121 - 216
Distance from material comb. (back/side/under)	mm	150 / 200 / 0
Distance to material comb. (front/top)	mm	500 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Ducting outlet (C)	Ø mm	80
Ductable up to	m	8
Appliance Type (tightness)	Type	CC50

PLUS

- 5 stars D.M. 186
- Back exhaust
- Go Fast - Faster pellet ignition
- Airtech - Automatic brazier cleaning
- UPS Ready
- Duction with 1 independent motor
- Remote control (optional)
- Sealed Chamber
- Cast iron burning pot

AVAILABLE FINISHES

7025068		Steel Light Bronze	EAN 8053859021780
7025069		Steel Titanium	EAN 8053859021797
7025070		Cast Iron Black	EAN 8053859021803

OPTIONAL

5024010	Remote control with thermostat	EAN 8053859020943
5024006	Kit ups ready	EAN 8053859020448

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BlmSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 16510-1:2022 / EN 16510-2-6:2022
CE



STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	126	68
	Volume (m ³)	0,69	
	Gross weight (kg)	110	
	Net weight (kg)	100	

STORAGE

	N° (max)
	2
MAX 2	
1	

TRANSPORT

60 pz