



Actinic BL TL(-K) / TL-D(-K)

Actinic BL TL-DK 36W/10 1SL/25

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Lamp Current (Nom)	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	0.865 A	
Life to 50% Failures (Nom)	9,000 hour(s)	Voltage (Nom)	
Useful Life (Nom)	5,000 hour(s)	50 V	
Light Technical		Mechanical and Housing	
Color Code	10	Bulb Shape	T26
Color Designation	Actinic	Net Weight (Piece)	68.900 g
Chromaticity Coordinate X (Nom)	225	Approval and Application	
Chromaticity Coordinate Y (Nom)	230	Mercury (Hg) Content (Nom)	8.0 mg
Operating and Electrical		UV	
Power Consumption	36 W	UV-A Radiation 100Hr (IEC)	8.8 W


Actinic BL TL(-K) / TL-D(-K)

Product Data	
Order product name	Actinic BL TL-DK 36W/10 1SL/25
Full product name	Actinic BL TL-DK 36W/10 1SL/25
Full product code	872790086083200
Order code	928019701003
Material Nr. (12NC)	928019701003


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900860832
Numerator - Packs per outer box	25
EAN/UPC - Case	8727900860849

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL-DK 36W/10 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm



Photometric data



Spectral Power Distribution Colour - Actinic BL TL-DK 36W/10 1SL/25

