NANOQUICK® Karta zastosowań

ZASTOSOWANIE

NANOQUICK® PROTECT

	NANOQUICK® BETON	NANOQUICK® BRUK	NANOQUICK® BRUK GRANIT	NANOQUICK® BRUK P	NANOQUICK® BRUK WET	NANOQUICK® BRUK & BETON REPAIR	NANOQUICK® PIASKOWIEC	NANOQUICK® PIASKOWIEC REPAIR	NANOQUICK® PIASKOWIEC FROST	NANOQUICK® MINERAL	NANOQUICK® MINERAL HD	NANOQUICK® MINERAL WET	NANOQUICK® MINERAL REPAIR	NANOQUICK® MINERAL FROST	NANOQUICK® CERAMIKA OIL	NANOQUICK® CERAMIKA HD	NANOQUICK® CERAMIKA HDR	NANOQUICK® GIPSUM	NANOQUICK® GRESUM	NANOQUICK® GRESUM HD	NANOQUICK® FUGA	NANOQUICK® GLASS	NANOQUICK® PEBBLES WHITE	NANOQUICK® GNEJS	NANOQUICK® GNEJS WET	NANOQUICK® DREWNO	NANOQUICK® BRUK+	NANOQUICK® BRUK W+	NANOQUICK® CERAMIKA+	NANOQUICK® CERAMIKA W+	NANOQUICK® MINERAL+	NANOQUICK® FUGA+	NANOQUICK® GLASS+	NANOQUICK® GNEJS+	NANOQUICK® ANTIALG+
Chłonność materiałowa																																			
Nisko Chłonne	■		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Chłonne	●	●	■	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	■	●	●	●	●	●	●	●	●	●	●	●	●	●
Materiały																																			
Wyroby Betonowe, Prefabrykaty	●		■	●	●	●	■		■		■		■		■		■		■		■		■		■		●	●	■		■		■		●
Kostka brukowa	■	●	■	●	●	●	■		■		■		■		■		■		■		■		■		■		●	●	■		■		■		●
Kostka granitowa, granity	■		●				■		■		■	●	●	●	■		■		■		■		■		■		■		■		■		■		●
Piaskowiec kwarcowy	■		■				●	●	●		■	●	●	●	■		■		■		■		■		■		■		■		■		■		●
Piaskowiec szarogłazowy	■		■				●	●	●		■	●	●	●	■		■		■		■		■		●		■		■		■		■	●	●
Wapień	■		■				■		■	●	●	●	●	●	■		■		■		■		■		●		■		■		■		●	●	●
Marmur	■		■				■		■	●	●	●	●	●	■		■		■		■		■		●		■		■		■		●	●	●
Granit	■		●				■		■		●	●	●	●	■		■		■		■		■		●		■		■		■		●	●	●
Trawertyn	■		■				■		■	●	●	●	●	●	■		■		■		■		■	●	●		■		■		■		●	●	●
Gnejs	■		■				■		■	●	●	●	●	●	■		■		●	●	■		■	●	●		■		■		■		●	●	●
Łupki	■		■				■		■	●	●	●	●	●	■		■		●	●	■		■	●	●		■		■		■		●	●	●
Szkło i elementy szklane	■		■				■		■		■		■		■		■		■		■	●	■		■		■		■		■		■	●	■
Ceramika, klinkiery, dachówki	■		■				■		■		■		■		●		■		■		■		■		■		■		■	●	●		■		●
Ceramika, gresy, płytki	■		■				■		■		●	●	●	●	■	●	●		●	●	■		■		■		■		■		■		●		■
Fugi mineralne	■		■				■		■		■	●	●	●	■	●	●		■		●		■		■		■		■		■		●	●	■
Drewno surowe	■		■				■		■		■		■		■		■		■		■		■		■		●		■		■		■		●
Wyroby gipsowe	■		■				■		■		■		■		■		■	●	■		■		■		■		■		■		■		●		●
Inne powierzchnie mineralne (zlepieniec, ortokwarcyt, kreda, dolomit, margiel, bazalt, gnejs, kwarcyt, onyks)	■		■				■		■		●	●	●	●	■		■		■		■		■		●	●	■		■		■		●		●
Wyroby otoczone białe Włochy, Macedonia, Grecja, Turcja)	■		■				■		■		■		■	●	■		■		■		■		■	●	■		■		■		■		●		●
Informacje dodatkowe																																			
Dodatek do masy	■		■				■		■		■		■		■		■		■		■		■		■		■		■		■		■		■
Szkliwione szlifowane	■		■				■		■		■		■		■		■		■		■		■		■		■		■		■		■		■

TEMPERATURY

Temperatury przechowywania																																				
max 30°C	■		■		●		■		■	●	●		■	●	■		■		■		●		■	●	■		■		■		■		■		■	■
max 35°C	●	●	●	●		●	●	●	●		■	●	●		●	●	●	●	●	●		●	●		●	●	●	●	●	●	●	●	●	●	●	●
min 2°C	●	●	●	●	●	●	●	●	■	●	■	●	●		●		■	●	■		●		●	●	●	●	●	●	●	●	●	●	●	●	●
min -5°C	■		■		■		■		●		●	■	■	●	■	●	●		●	●	■	●	■		■		■		■		■		■		■	■
Temperatury (przy nakładaniu)																																				
24 Miesiące	●		■	●	■	●	■	●	●		●	●	●	●	■	●	●		■		■	●	■		■		■		■		■		■		■	■
36 Miesiące	■		●		●		●		■	●	■		■		●		■	●	●	●	●		●	●	●	●	●	●	●	●	●	●	●	●	●

MAGAZYNOWANIE

Magazynowanie																																				
max 55°C	■		■		■		■		■		■		■		■		■		■		■		■		■		■		■		■		■		■	■
max 40°C	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Właściwości chemiczne																																				
Palność	■		■		●		■		■		●	●	■		■	●	●		●	●	■	●	■		●		■		■		■		■		■	■