



Supertec 5W-30

SPECIFICATIONS

Engine:	gasoline, diesel
SAE:	5W-30
API:	SN / CF
ACEA:	A3/B3 / A3/B4

APPROVALS AND CONFORMITY

VW 502.00 VW 505.00 VW 501.01 VW 505.00 MB 229.3 MB 229.5 BMW Longlife-01 PSA B71 2296
PSA B71 2300 Renault RN0700 Renault RN0710 GM LL-B-025 Porsche A40

CHARACTERISTICS

- Extreme wear protection;
- Excellent viscosity-temperature behavior;
- Minimal frictional loss;
- Very high cleaning capability;
- Low volatilization loss;
- High oxidation and temperature stability.

EFFECTS

- Reduces fuel consumption according API EC and reduces exhaust emission;
- Excellent cold starting properties - rapid supply of all points of lubrication;
- Very good operating reliability;
- Optimal engine cleanliness;
- Lowest oil consumption;
- High margin of performance and high product stability;
- Extended oil change intervals;
- Prevents black sludge formation;
- All-year operation.

DISPOSAL

- WOLVER SuperTec SAE 5W-30 is assigned to category 2 of used oils and thus is free for disposal.

TYPICALS

Kinematic viscosity at 100 °C	11.6 mm²/s
Viscosity index	163
Pour point	-36 °C
Viscosity CCS at -30 °C	6200 mPa·s
TBN	9.3 mgKOH/g
Flash point	220 °C
Density at 15.6 °C	843 kg/m³

DESCRIPTION

Wolver Supertec SAE 5W-30 is a hightec synthetic lightrun motor oil especially developed for heavily stressed petrol and diesel car motors.

Wolver Supertec SAE 5W-30 meets the manufacturers` high quality demands for cars. It is excellently applicable for long oil changing intervals and for motors with direct injection. Ideal for hard use on motorways and over short distances.

Utilization

- High-performance and normal four-stroke petrol engines;
- with multivalve technology;
- with turbo charging;
- with catalyst technology;
- Passenger car diesel engines;
- with turbo charging;
- Direct-injection;
- with CDi-technology;
- with catalyst technology.

Miscibility

Wolver Supertec SAE 5W-30 is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of Wolver Supertec SAE 5W-30 it is recommendable to use only Wolver Supertec SAE 5W-30 when refilling.

1L - Can	4137	4260360941375
4L - Can	4139	4260360941399
20L - Pail	4067	4260360940675
60L - Barrel	4266	4260360942662

208L - Barrel	4037	4260360940378
---------------	------	---------------
