

# TAEKI5® CUT RESISTANT SLEEVE

Ref. 4945 (4925-4935-4960)



# SIZES AND REFERENCES

| Size  | Ref  | Bar codes     |
|-------|------|---------------|
| 25 cm | 4925 | 3435241049254 |
| 35 cm | 4935 | 3435241049353 |
| 45 cm | 4945 | 3435241049452 |
| 60 cm | 4960 | 3435241049605 |



## GENERAL DESCRIPTION AND MATERIALS

- Heat and cut resistant sleeve
- Grey color

• Thumb hole ( <u> except for Ref. 4925</u>)

## SPECIFIC FEATURES

- High resistance to abrasion
- Very high resistance to cut

- Resistance to heat up to 100°
- Tightening on cuff for sleeve 25cm

### MAIN APPLICATION FIELDS

- Car industry
- Food processing industry

- Glass manufacture
- Steel manufacture

## PACKING

Bag with 10 pieces

• 100 pieces in a carton

### STANDARDS

This glove is in conformity witht the prototype of personal protective equipment which corresponds to

EC Type-examination certificates N° 0075/1747/162/01/18/0208 & 0075/1747/162/01/18/0167

Issued by CTC (notified body n° 0075) EN 420:2003+A1:2009

EN 388:2016



4X4XC

- Abrasion = 4/4
- Blade cut (coupe-test) = X/5
- Tear = 4/4
- Puncture = X/4
- Cut resistance TDM = C

EN 407:2004



X1XXXX

- Resistance to **flammability** = X/4
- Resistance to contact heat= 1/4
- Resistance to **convective heat**= X/4
- Resistance to radiant heat = X/4
- Resistance to small splashes of molden metal = X/4
- Resistance to large splashes of molden metal = X/4

SACLA INTERNATIONAL – Z.I. de Rosarge – 01700 LES ECHETS – MIRIBEL – FRANCE

Tel.: (33) 04 72 26 59 60 - Fax.: (33) 04 72 26 59 61 - Mail: export@sacla-international.com