



Myers 5MP Turret

ENG



- 5.0 Mp resolution
- High sensitivity
- POE IP camera
- Smart functions support
- IP67 rating
- IR LED
- 3-Axis mounting
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Remote access to the device with Partizan MAC

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



IP Camera		
Model		Myers
Version		5MP Turret
SKU		5856
Image Sensor		
Sensor		1/2.8" CMOS Sensor
Pixel Size, µm		2.8x2.8
Resolution, pixels@fps	Mainstream (max)*	PAL: 5MP@25, 4MP@25, 3MP@25; NTSC: 5MP@30, 4MP@30, 3MP@30;
	Substream (max)*	PAL: D1@25, HD1@25, CIF@30 NTSC: D1@30, HD1@30, CIF@30
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0.01
Dynamic range WDR, dB		72
S/N ratio, dB		48
Video functions		AES, AGC, AWB, BLC, OSD, PrivacyMasks
Smart functions in camera		Human detection
Smart functions when using together with Cloud-series NVR		Human detection / Human Perimeter Intrusion Detection / Human Line Crossing Detection
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		2.8
Iris, F		1,6
Angle of View, °	Horizontal	88
	Vertical	58
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control, Manual/Auto		-
IR LED		
Distance, m		≤25
Number of LEDs, pcs.		Double light, 3015Ux2
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		Partizan MAC protocol/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP/HTTP/HTTPS/TCP/IPV4
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		DHCP (Auto)
Username		admin
Password		admin
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://IPaddress:port/user=admin&password=admin&channel=1&stream=0.sdp?
Snapshot capture link		http://IPaddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin
Control port		34567
Configuration software		Partizan (Setup Tool), Partizan Device Manager, Web interface
Monitoring program		Partizan
Mobile software (support)		Partizan
Protocol integration		Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Housing	Φ 94 x 69
	Bracket	Ø94
Weight, g		450
Common		
Power Supply	DC12V, A	1
	PoE Class/W	0/5
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	-
	Inputs	-
	Built-in speaker	-
Memory card		-
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-/+
IP rating		67
IK rating		-
Operating temperature, °C		-30 - +60
Warranty, years		3